




	PCB CLEANER PCB-CLEANER/1000 METAL CANISTER 1000 ml AG TERMOPASTY	CLEANING STICKS CLEANING-STICKS/20 AG TERMOPASTY	IP CAMERA DS-2CD1023G2-I(2.8MM)PL - 1080p Hikvision
			
	4296.15 HUF 4296.15 HUF	2134.62 HUF 2134.62 HUF	51346.15 HUF 51346.15 HUF
Standard	IP
In package	...	20 pcs - The price for package	...
Package	Metal canister 1000 ml
Resolution	1920 x 1080 - 1080p , 1280 x 720 - 720p
Application	Ideal for removing dirt from optical components	<ul style="list-style-type: none"> • Cleaning the optics • Cleaning heads in dot matrix printers • Cleaning the mechanical components of printers (including paper feeding mechanisms, print head drives) • LCD displays cleaning • Cleaning keyboards, mice and other electronic equipment with hard-to-reach areas 	...
Sensor	1/2.9 " Progressive Scan CMOS
Lens	2.8 mm
View angle	104 °
Range of IR illumination	30 m
Memory card slot	—
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	—
Audio	—
Main stream frame rate	25 fps @ 1080p
Network interface	10/100 Base-T (RJ-45)
WEB Server	Built-in
Max. number of on-line users	6
ONVIF	✓
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default admin user / password	admin / -
Default IP address	192.168.1.64
Web browser access ports	80
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	8000
Port ONVIF	80

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

RTSP URL	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • BLC - configurable Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Day/night mode • Mirror - Mirror image • Configurable Privacy Zones • Smart motion detection (with recognizing people and vehicles) • Sharpness - sharper image outlines
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 410 mA
Power consumption	<ul style="list-style-type: none"> • ≤ 5 W @ 12 V DC • ≤ 6.5 W @ PoE (802.3af)
Housing	Compact - Metal + Plastic
Color	White
"Index of Protection"	IP67
Operation temp	-30 °C ... 60 °C
Weight	0.857 kg	...	0.27 kg
Dimensions	199 x 116 x 62 mm	123 x 12 x 4 mm	171 x 70 x 66 mm
Supported languages	Polish
Manufacturer / Brand	AG TERMOPASTY	AG TERMOPASTY	Hikvision
SAP Code	311327275
Guarantee	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00