

	COAXIAL CABLE RF-7 50 Ω	NO-TOUCH DOOR EXIT BUTTON ATLO-NB-17
		
	1.95 EUR 1.95 EUR	8.28 EUR 8.28 EUR
Contact type	...	NO, NC
In section	100 m . Price for 1m when buying a whole roll	...
Detection range	...	0 mm ... 120 mm
Relay maximal load	...	3 A / 30 V DC
Inner conductor	Ø 1.85 mm Cu ± 0.05 mm - Cu stranded wire	...
"Index of Protection"	...	IP40
Dielectric	Ø 5 mm - Physical foam	...
Power supply	...	12 V DC
Shield	Double-sided foil - Cu/PET/Cu	...
Braid	80 % Cu	...
Current consumption	...	<ul style="list-style-type: none"> • 20 mA (Standby mode) • 40 mA (operation)
Impedance	50 Ω	...
Material	...	Aluminum + Plastic
Outer coating	Ø 7.3 mm ± 0.2 mm PE - Black	...
Color	...	Silver + Black
Weight	...	0.07 kg
Dimensions	...	86 x 86 x 28 mm
Manufacturer / Brand	...	ATLO
Main features	<ul style="list-style-type: none"> • low attenuation • perfect matched • high screening efficiency • it can be used in WLAN 2,4GHz and 5GHz installations • Operation temp : -30 °C ... 70 °C 	Blue backlight + green
Cable attenuation at 100m section	2 dB @ 10 MHz 6.4 dB @ 100 MHz 9.1 dB @ 200 MHz 14.1 dB @ 500 MHz 20.9 dB @ 800 MHz 25.9 dB @ 1 GHz 31 dB @ 1.5 GHz 35 dB @ 2 GHz 39 dB @ 2.5 GHz	...

Maximum transmitted power	3.27 kW @ 10 MHz 1.025 kW @ 100 MHz 0.693 kW @ 200 MHz 0.452 kW @ 500 MHz 0.310 kW @ 800 MHz 0.253 kW @ 1 GHz 0.219 kW @ 1.5 GHz 0.195 kW @ 2 GHz 0.175 kW @ 2.5 GHz	...
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00