






	TV OR MONITOR MOUNT MC-711N MACLEAN	SWITCH POE GTX- C1-10-8G2G 8-PORT	FLUSH BOX PK-60F/K- G/S/EPN Elektro-Plast	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1500T- A-0280B-S2 - 4.7 Mpx 2.8 mm DAHUA	SILVER OXIDE BATTERY BAT-392/384 ENERGIZER
					
	23.49 AUD 23.49 AUD	142.42 AUD 142.42 AUD	1.74 AUD 1.74 AUD	131.38 AUD 131.38 AUD	2.20 AUD 2.20 AUD
Rated voltage	1.55 V
Number of sections	1
Standard	AHD, HD-CVI, HD-TVI, CVBS	...
Sensor	1/2.7" CMOS	...
Type (size)	SR736 / SR41 / 392 / 384
Matrix size	5 Mpx	...
LAN ports	...	• 8 x RJ45 (1 x Hi-PoE + 7 x PoE (802.3af/at)), • 2 x RJ45 - Uplink
Mounting standard	VESA : 75, 100, 200x100, 200, 300x200, 300, 400x200, 400x300, 400
Material	halogen free and inflammable
Screen size range	26" ... 55"
Bearing capacity	30 kg
Montage hole diameter	Ø 68 mm
Distance from mounting surface	63 ... 415 mm
Management	...	—
Tilt adjustment	-15° ... 10°
Resolution	2880 x 1620 - 4.7 Mpx - HD- CVI only : Aspect Ratio 16 : 9, 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p 960 x 576 - 960H	...
Lens	2.8 mm	...
Horizontal rotation	-90° ... 90°
Rotation in the plane of the screen	± 3°
LED diodes	...	Power, V - VLAN (Port Isolation), S - Extend, PoE, Link/Act, Speed
Transmission speed	...	10 / 100 / 1000 Mbps : 2 x Port LAN - Uplink + 8 x Port LAN & PoE
View angle	• 111° (manufacturer data) • 104° - HD-CVI, 91° - HD- TVI, 90° - AHD (our tests result)	...
Range of IR illumination	30 m	...
IR illuminator power adjustment	Automatic	...
Operation modes	...	• N - Normal - the device operates as normal PoE switch • V - VLAN (Port Isolation) - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports • S - Extend - Range : 250 m @ 10 Mbps

Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...
Audio	Microphone built-in, HD-CVI only	...
S/N ratio	> 65 dB	...
OSD menu	✓	...
Maximal output power	...	• 60 W / port Hi-PoE - Port 1 • 30 W / port PoE - 2 ... 8 ports
Maximal total power	...	120 W
MAC addresses table	...	2k
Main features	...	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Full Duplex: IEEE802.3x, Half Duplex: Back Pressure • Auto-learning and Auto-aging functions support for MAC addresses • PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • MTBF (Mean Time Between Faults) : 50000 h 	<ul style="list-style-type: none"> • Flush-mounted, deep, for hollow walls • 850 °C flammability index • 2 special screws with holders to fastening to the wall - included
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Sharpness - sharper image outlines • AGC - Automatic Gain Control • Privacy zones • Mirror - Mirror image • Auto White Balance 	...
Certificates	...	CE, FCC Class B
Protections	...	Overvoltage ± 4 kV
Power consumption	≤ 3.2 W	...
Power supply	...	100 ... 265 V AC	...	12 V DC / 270 mA	...
Housing	Compact, Metal	...
Color	Black	...	Yellow	White	...
Operation temp	...	-10 °C ... 45 °C
"Index of Protection"	—	IP67	...
Operation temp	-40 °C ... 60 °C	...
Weight	2.93 kg	0.79 kg	0.026 kg	0.37 kg	0.001 kg
Dimensions	455 x 420 x (63 ... 415) mm	210 x 150 x 35 mm	Ø 60 x 61 mm - Internal dimensions Ø 71 x 62 mm - External dimensions	Ø 73 x 176 mm	Ø 7.9 x 3.6 mm
Manufacturer / Brand	MACLEAN	...	Elektro-Plast	DAHUA	ENERGIZER
Guarantee	2 years	2 years	2 years	3 years	2 years