

	IP SPEED DOME CAMERA INDOOR SD29404DB-GNY WizSense - 3.7 Mpx 2.8 ... 12 mm DAHUA	ANGULAR COUPLER LMA- LX50/B
		
	852.06 AUD 852.06 AUD	2.92 AUD 2.92 AUD
Standard	IP	...
Length	...	100 mm
Width	...	100 mm
Depth	...	27.5 mm
Material	...	PVC
Resolution	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	...
Sensor	1/2.8 " Progressive Scan CMOS	...
Lens	2.8 ... 12 mm	...
View angle	95 ° ... 30 °	...
Optical zoom	x 4	...
Digital zoom	x 16	...
Range of IR illumination	50 m	...
Video output	—	...
Rotation speed (manual control)	<ul style="list-style-type: none"> • 0.1 °/s ... 100 °/s (horizontal), • 0.1 °/s ... 60 °/s (vertical) 	...
Preset rotation speed	<ul style="list-style-type: none"> • 100 °/s (horizontal) • 60 °/s (vertical) 	...
Horizontal rotation range	0 ° ... 360 ° - Rotation of the head is limited by stops	...
Vertical rotation range	0 ° ... 90 °	...
RS-485	—	...
Number of presets	300	...
Horizontal scan	✓	...
Route settings	5	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	2 / 1	...
Main stream frame rate	25 fps - 3.7 Mpx	...
Memory card slot	Micro SD card support up to 256GB	...
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in, NVR compliance	...
Max. number of on-line users	20	...
ONVIF	✓	...
Audio	<ul style="list-style-type: none"> • Microphone built-in, • External microphone input • Audio output • Audio transmission via network • Bi-directional audio streaming support 	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile phones support	Port 37777 • Android: Free application DMSS • iOS (iPhone): Free application DMSS	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Default IP address	192.168.1.108	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Intelligent image analysis	<ul style="list-style-type: none"> • intrusion • crossing the line (tripwire) • detection of crossing a virtual fence • abandoned/missing object • fast moving • detection of people gathering • face detection - advanced face capture features 	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • EIS - Electronic Image Stabilization • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • SMD 3.0 - searching for an object classified as: human, motor vehicle • Day/night mode • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Configurable Privacy Zones • • Intelligent 3D Positioning System 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 830 mA 	...
Power consumption	≤ 10 W	...
Housing	Speed Dome, Plastic	...
Color	White + Black	Black
"Index of Protection"	—	...
Operation temp	-30 °C ... 50 °C	...
Weight	0.7 kg	0.03 kg
Dimensions	Ø 132 x 117 mm	...
Supported languages	Polish, English	...
Manufacturer / Brand	DAHUA	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00