

	TERMINAL COVER TBC-09	ADAPTER WT-4.4/GT-55	UNIVERSAL MIDDLE CLAMP PV-KSU/50/B FOR SOLAR PANELS	SMART ACTION TRIGGER ACTIONBOX-S/BLEBOX Wi-Fi, 230 V AC	GROUNDING RESISTANCE METER UT-522 UNI-T
					
	222.86 HUF 222.86 HUF	293.33 HUF 293.33 HUF	364.76 HUF 364.76 HUF	7899.05 HUF 7899.05 HUF	78061.90 HUF 78061.90 HUF
Application	Power supply adapters of the RSP-200/320 and LRS-200/350 series	controlling devices, triggering actions	...
Material	Aluminum
Rated voltage	230 V AC	...
Height	21.5 mm
Maximal total load	—	...
Hole diameter	9 mm
Total maximal current	—	...
mounting screw	—
Number of inputs	1	...
Number of outputs	0	...
Connector type	screw terminals	...
Connector type	...	Adapter : Plug : 6.5 / 4.3 / 1.4 mm , Socket : 5.5 / 2.1 mm
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g	...
Material	Plastic, (transparent)	Metal + PET
Mobile phones support	<ul style="list-style-type: none"> The wBox free application on Android The wBox free application on iOS 	...
Resistance measurement	40 Ω ± (2% + 20) @ 0.01 Ω , 400 Ω ± (2% + 3) @ 0.1 Ω , 4000 Ω ± (2% + 3) @ 1 Ω • Auxiliary resistance : 500 Ω ± 5 % • Measuring voltage : ≤ 10 V AC @ ~820 Hz
Ground voltage measurement	400 V ± (1.0% + 6) @ 1 V
Automatic change of measuring ranges	—
RS-232	—
USB	—
Housing	Plastic	...
"Index of Protection"	IP20	...
Color	Black	Black	...
Main features	...	<ul style="list-style-type: none"> Very easy and quick assembly Corrosion resistance Cooperation with DAHUA switches and recorders powered by 48V DC 	Ground pins	<ul style="list-style-type: none"> Local control by physical button, schedule, timer, remote access, voice control, µWiFi technology support 	<ul style="list-style-type: none"> Hold - stopping the meter reading, The measurement can be performed in full or simplified configuration, Warning of poor connection of leads during measurement, Large, readable LCD display with backlight, Low battery level alarm, Aesthetic and solid construction, The set includes a practical case
Operation temp	-20 °C ... 50 °C	5 °C ... 40 °C

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Permissible relative humidity	≤ 80 % (non-condensing)
Power supply	6 x 1.5V, type AA/LR6/FR6 battery - included
Weight	...	0.005 kg	0.026 kg	0.024 kg	0.42 kg
Dimensions	89 x 10 x 4 mm	Ø 13 x 42 mm	50 x 36 x 24.5 mm	39 x 25 x 23 mm	160 x 100 x 70 mm
Manufacturer / Brand	BleBox	UNI-T
Guarantee	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00