

	IP VANDALPROOF CAMERA IPC-HDBW2241R-ZAS-27135-BLACK WizSense - 1080p, 2.7 ... 13.5 mm - MOTOZOOM DAHUA	SWITCH POE SPS-2P/1SFP 2-PORT + SFP	STYROFOAM PLUG SM-50/EPN*P4 Elektro-Plast
			
	330.02 CHF 330.02 CHF	48.79 CHF 48.79 CHF	0.92 CHF 0.92 CHF
Standard	TCP/IP	...	...
LAN ports	...	2 x RJ45, PoE (802.3af/at)	...
Sensor	1/2.8 " Progressive Scan CMOS	...	...
Matrix size	2.1 Mpx	...	...
In package	...	...	4 pcs The price for package
Length	...	...	49 mm
Diameter	...	...	Ø 20 mm / Ø 24 mm
Management	...	—	...
Thickness of the Styrofoam	...	...	≥ 50 mm
Resolution	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	...	...
Diameter of the screw	...	...	Ø 4 mm ... Ø 5 mm
Lens	2.7 ... 13.5 mm - Motozoom	...	...
LED diodes	...	PWR - Power, FL - Link/Act port SFP, Speed - 1000 Mbps, Link/Act	...
View angle	• 108 ° ... 30 ° (manufacturer data) • 102 ° ... 31 ° (our tests result)	...	...
Range of IR illumination	40 m	...	...
RS-485 interface	—	...	...
Transmission speed	...	1 port SFP : 1000 Mbps + 2 LAN & PoE ports : 10 / 100 / 1000 Mbps	...
Maximal output power	...	25.5 W / port PoE	...
Maximal total power	...	51 W	...
MAC addresses table	...	1k	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	...
Certificates	...	CE	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...	...
Alarm inputs / outputs	1 / 1	...	...
Permissible relative humidity	...	10 % ... 90 %	...
Audio	• Microphone built-in, • External microphone input • Audio output • Bi-directional audio streaming support • Audio detection	...	...
Operation temp	...	-20 °C ... 70 °C	...
Network interface	10/100 Base-T (RJ-45)	...	...
Network protocols	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, NTP, Multicast, ICMP, IGMP	...	...
WEB Server	Built-in, Web Viewer	...	...
Max. number of on-line users	20	...	...
ONVIF	21.12	...	...
Main stream frame rate	25 fps @ 1080p	...	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	...	...
Default IP address	192.168.1.108	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default admin user / password	admin / - The administrator password should be set at the first start	...	...
Web browser access ports	80, 37777	...	...
PC client access ports	37777	...	...
Mobile client access ports	37777	...	...
Port ONVIF	80	...	...
RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...	...
Main features	• Motozoom lens • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Motion Detection • Configurable Privacy Zones • ICR - Movable InfraRed filter • Image rotation and mirror • SMD PLUS - searching for an object classified as: human, motor vehicle • IVS analysis : crossing the line (tripwire), intrusion - classification of people and vehicles	...	...
Power supply	• PoE (802.3af), • 12 V DC / 520 mA	52 V DC / 1.25 A (power adapter included) (2.5/5.5mm socket)	...
Power consumption	• ≤ 6.3 W @ 12 V DC, • ≤ 7.2 W @ PoE	...	...
Housing	Dome - Metal	...	...
Color	Black	...	...
"Index of Protection"	IP67	...	...
Vandal-proof	IK10	...	...
Operation temp	-30 °C ... 60 °C	...	...
Weight	0.51 kg	0.13 kg	0.004 kg / 1 pcs
Dimensions	Ø 122 x 89 mm	97 x 71 x 27 mm	...
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Romanian, Russian, Turkish, Ukrainian, Hungarian, Italian	...	...
Manufacturer / Brand	DAHUA	...	Elektro-Plast Nasielsk
Guarantee	3 years	2 years	2 years