



	<a href="#">IP CAMERA APTI-AI805VA2-28W-L Full-Color - 8.3 Mpx 4K UHD 2.8 mm</a>	<a href="#">EXTENDER HDMI+USB-EX-100-4K</a>
		
	854.59 DKK 854.59 DKK	1511.97 DKK 1511.97 DKK
Standard	TCP/IP	...
Matrix size	8.3 Mpx	...
Sensor	1/2.8 " SONY Starvis™ Back-illuminated CMOS	...
Supported HDMI resolutions	...	480p, 576i, 576p, 720p 1080i, 1080p, 4K x 2K, 4K UHD
Resolution	3840 x 2160 - 8.3 Mpx 4K UHD , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Maximal transmission range	...	<ul style="list-style-type: none"> <li>• 70 m UTP cat. 6 @ 4K UHD,</li> <li>• 70 m UTP cat. 5, 5e @ 1080p</li> <li>• 50 m UTP cat. 5e @ 4K UHD (our tests result)</li> </ul>
Lens	2.8 mm	...
View angle	105 °	...
White light LED illuminator range	30 m	...
Main features	...	<ul style="list-style-type: none"> <li>• Very good image quality with no visible distortions caused by compression</li> <li>• No delays in video transmission</li> <li>• No delays in mouse control operations</li> <li>• Transition of the HDMI signal in the transmitter</li> <li>• S/PDIF output</li> </ul>
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Main stream frame rate	25 fps @ 8.3 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
Memory card slot	—	...
Alarm inputs / outputs	—	...
Operation temp	...	-20 °C ... 60 °C
Permissible relative humidity	...	0 % ... 90 % (non-condensing)

Audio	<ul style="list-style-type: none"> <li>• External microphone input - Jack 3.5 mm socket</li> <li>• Audio output - Jack 3.5 mm socket</li> <li>• Audio transmission via network</li> <li>• Compliance with the AAC standard</li> </ul>	...
WEB Server	Built-in	...
Max. number of on-line users	10	...
ONVIF	19.12	...
RS-485 interface	—	...
Mobile phones support	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">BitVision</a></li> <li>• iOS (iPhone): Free application <a href="#">BitVision</a></li> </ul>	...
Default IP address	192.168.1.168	...
Default admin user / password	admin / admin The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	80	...
Mobile client access ports	80	...
Port ONVIF	80	...
RTSP URL	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream	...

Main features	<ul style="list-style-type: none"> <li>• WDR - 140 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• Flicker Control - The technology eliminates the tiring eyes flickering image effect</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• ICR - Movable InfraRed filter</li> <li>• Privacy zones</li> <li>• Image rotation and mirror</li> <li>• Sharpness - sharper image outlines</li> <li>• Intelligent image analysis : intrusion, crossing the line (tripwire), detection of people gathering, loitering detection, motion detection based on human detection</li> <li>uploading face captures to FTP</li> </ul>	<ul style="list-style-type: none"> <li>• Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse</li> </ul>
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 450 mA</li> </ul>	<ul style="list-style-type: none"> <li>• Transmitter 5 V DC / 2 A (power adapter included)</li> <li>• Receiver 5 V / 2 A (power adapter included)</li> </ul>
Power consumption	≤ 5.4 W	...
Housing	Dome - Metal	...
Color	White	...
"Index of Protection"	IP67	...
Vandal-proof	—	...
Operation temp	-20 °C ... 60 °C	...
Weight	0.5 kg	0.29 kg
Dimensions	Ø 97 x 91 mm	150 x 107 x 28 mm - Transmitter or receiver dimensions
Supported languages	Polish, English, Bulgarian Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian	...
Manufacturer / Brand	APTI	...
Guarantee	2 years	2 years