

|                                    |   |   |
|------------------------------------|---|---|
|                                    | <a href="#">BATTERY 12V/12AH-MWL</a>  | <a href="#">NVR BCS-V-NVR3204-4K-AI 32 CHANNELS +eSATA BCS View</a>   |
|                                    |  |    |
|                                    | 27.36 CHF<br>27.36 CHF  | 1075.42 CHF<br>1075.42 CHF  |
| Standard                           | ...   | TCP/IP  |
| Battery capacity                   | 12 Ah   | ...   |
| Rated voltage                      | 12 V  | ...   |
| Battery charging current           | max. 4.2 A  | ...   |
| Supported resolutions              | ...   | max. 12 Mpx - 4000 x 3000 px  |
| Battery type                       | Maintenance-free AGM (Absorbent Glass Mat) battery                                | ...   |
| Connector                          | T1 type   | ...   |
| Battery lifetime                   | 10 ... 12 years   | ...   |
| Video outputs                      | ...   | 1 pcs HDMI 4K<br>1 pcs HDMI<br>1 pcs VGA<br>1 pcs CVBS - BNC socket<br>There is a possibility to configure a SPOT function on one of the output   |
| Audio support                      | ...   | 32 Channels - Audio from cameras  |
| Audio inputs                       | ...   | 1 pcs CINCH   |
| Audio outputs                      | ...   | 1 pcs CINCH   |
| Image compression method           | ...   | H.265+ / H.265 / H.264+ / H.264   |
| Supported hard drives              | ...   | 4 x 8 TB SATA + 1 x eSATA   |
| Recording modes                    | ...   | Manual, Motion Detection, Schedule  |
| Network protocols                  | ...   | TCP/IP, DHCP, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP, HTTPS, P2P, ONVIF   |
| External storage devices backup    | ...   | Backup to USB drive (pendrive, external drive)  |
| Default admin user / password      | ...   | admin / -<br>The administrator password should be set at the first start  |
| Default IP address                 | ...   | DHCP or 192.168.1.64  |
| Web browser access ports           | ...   | 80  |
| PC client access ports             | ...   | Port no.: 8000 or access by a cloud (P2P)   |
| Mobile client access ports         | ...   | 8000  |
| RTSP URL                           | ...   | <ul style="list-style-type: none"> <li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream</li> <li>• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream</li> </ul> |
| Searching and playback the records | ...   | Records searching: by time and events type. Records playback: forward, backward, fast, slow   |

|                                 |                  |  |
|---------------------------------|------------------|--|
| Bitrate                         | ...              | max. 256 Mbps  |
| Intelligent image analysis      | ...              | crossing the line (tripwire), intrusion  |
| Network functions               | ...              | Live image view, Playback the records, Backup the records  |
| ONVIF                           | ...              | ✓  |
| Mobile phones support           | ...              | Port no.: 8000 or access by a cloud (P2P)<br>• Android: Free application <a href="#">BCS View</a><br>• iOS (iPhone): Free application <a href="#">BCS View</a> |
| Alarm inputs / outputs          | ...              | 16 / 4   |
| PTZ control                     | ...              | IP Speed Dome Cameras  |
| USB                             | ...              | 2 pcs USB 2.0<br>1 pcs USB 3.0   |
| Motion Detection                | ...              | ✓  |
| Mouse support                   | ...              | ✓  |
| IR remote controller in the set | ...              | —  |
| Main features                   | ...              | POS - support the machines installed in the points of sales and displaying the date from them as overlaid text on selected channel window                      |
| Operation temp                  | ...              | -10 °C ... 55 °C   |
| Power supply                    | ...              | 100 V ... 240 V AC @ 50 / 60 Hz  |
| Weight                          | 3.63 kg          | 4.33 kg  |
| Dimensions                      | 151 x 98 x 96 mm | 440 x 400 x 71 mm  |
| Supported languages             | ...              | Polish, English  |
| Manufacturer / Brand            | ...              | BCS View   |
| Guarantee                       | 2 years          | 3 years  |

