



	IP CAMERA APTI-RF42MAP-37 Wi-Fi, PINHOLE - 4 Mpx 3.7 mm	PROXIMITY CARD HOLDER CH-1
		
	1892.98 CZK 1892.98 CZK	17.30 CZK 17.30 CZK
Material	...	Plastic
Standard	TCP/IP	...
Sensor	1/3 " Progressive Scan CMOS	...
Matrix size	4 Mpx	...
Resolution	2688 x 1512 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Lens	3.7 mm (pinhole)	...
View angle	• 70 ° (manufacturer data) • 90 ° (our tests result)	...
S/N ratio	> 52 dB	...
Min. illumination	0.01 Lux @ F1.6 (AGC off)	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	1 / -	...
Main stream frame rate	25 fps - 4 Mpx	...
Network interface	• 10/100 Base-T (RJ-45) • Wi-Fi - IEEE 802.11 b/g/n	...
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, SMTP, UDP	...
Audio	• Audio input - Jack 3.5 mm socket • Audio output - Jack 3.5 mm socket • Bi-directional audio streaming support	...
ONVIF	2.4	...
RS-485 interface	—	...
Memory card slot	Micro SD memory cards up to 512GB support (possible local recording)	...
Mobile phones support	Port no.: 80 or access by a cloud (P2P) • Android: Free application BitVision • iOS (iPhone): Free application BitVision	...
Default IP address	192.168.1.168	...
Default admin user / password	admin / admin	...
Web browser access ports	80	...
PC client access ports	80	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

WEB Server	Built-in Built-in	...
Mobile client access ports	80	...
Max. number of on-line users	10 10	...
Port ONVIF	80	...
RTSP URL	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream	...
Main features	<ul style="list-style-type: none"> • Wi-Fi Module - IEEE 802.11 b/g/n, Range : 50 m (open area) • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ROI - improve the quality of selected parts of image • Flicker Control - The technology eliminates the tiring eyes flickering image effect • F-DNR (Defog) - Reduction of image noise caused by precipitation • Possibility to change the resolution, quality and bit rate • Motion Detection • Privacy zones • Configurable: brightness, contrast, saturation • Mirror - Mirror image • Sharpness - sharper image outlines • Intelligent image analysis : intrusion 	...
Power supply	12 V DC / 190 mA	...
Power consumption	≤ 2.3 W	...
Housing	Mini - Metal	...
Color	Black	Colorless
Operation temp	-20 °C ... 60 °C	...
Weight	0.14 kg	0.001 kg
Dimensions	37.5 x 37.5 x 30 mm	96 x 63 x 4 mm
Supported languages	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian	...
Manufacturer / Brand	APTI	ROGER
Guarantee	2 years	2 years