



	<a href="#">SWITCH POE IP-5-11-E 5-PORT ATTE</a>	<a href="#">IP CAMERA TC-C34QN SPEC:15W/E/Y/2.8MM/V4.2 - 4 Mpx 2.8 mm TIANDY</a>
		
	128.50 EUR 128.50 EUR	104.69 EUR 104.69 EUR
LAN ports	<ul style="list-style-type: none"> <li>• 1 x RJ45 10/100 Base-T - Uplink</li> <li>• 5 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE</li> </ul>	...
Standard	...	IP
Management	—	...
Sensor	...	1/2.9 " Progressive Scan CMOS
LED diodes	Power, LAN	...
Transmission speed	10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports	...
Resolution	...	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	...	2.8 mm
View angle	...	100 °
Range of IR illumination	...	50 m
White light LED illuminator range	...	15 m
Memory card slot	...	—
Image compression method	...	S+265 / H.265 / H.264
Maximal output power	<ul style="list-style-type: none"> <li>• 40 W @ Passive PoE - 1 ... 4 ports,</li> <li>• 70 W @ Passive PoE - Port 5,</li> <li>• 30 W @ PoE (802.3af/at) - 1 ... 5 ports</li> </ul>	...
Alarm inputs / outputs	...	—
Maximal total power	96 W	...
Audio	...	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio transmission via network</li> </ul>
Main stream frame rate	...	25 fps @ 4 Mpx
Network interface	...	10/100 Base-TX (RJ-45)
WEB Server	...	Built-in

Max. number of on-line users	...	2
ONVIF	...	✓
Mobile phones support	...	Port no.: 3000 or access by a cloud (P2P) • Android: Free application <a href="#">EasyLive Plus</a> • iOS (iPhone): Free application <a href="#">EasyLive Plus</a>
Access from PC	...	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a>
Operation modes	<ul style="list-style-type: none"> <li>• Normal : 100 m @ 10/100 Mb/s - 1 ... 5 ports</li> <li>• Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - Port 5</li> <li>• Port LAN 6 - Uplink</li> </ul>	...
Default IP address	...	DHCP or 192.168.1.2
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 433, 3000, 3001, 3002, 23002
Mobile client access ports	...	3000, 3001
Main features	<ul style="list-style-type: none"> <li>• Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port)</li> <li>• The output PoE voltage is equal to the input voltage</li> <li>• The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports</li> <li>• The modular design streamlines service tasks and enables quick and easy system expansion</li> <li>• The raster system of module assembly facilitates the expansion of the device by further modules</li> </ul>	...
PC client access ports	...	3000, 3001
Port ONVIF	...	80

Intelligent image analysis	...	<ul style="list-style-type: none"> <li>• crossing the line (tripwire)</li> <li>• intrusion</li> </ul>
Main features	...	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• Day/night mode</li> <li>• Possibility to change the resolution, quality and bit rate</li> </ul>
Power supply	230 V AC - cable terminals	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 590 mA</li> </ul>
Power consumption	...	≤ 7 W
Housing	...	Compact - Metal + Plastic
Color	...	White
"Index of Protection"	...	IP67
Mechanical protection class	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	1.4 kg	0.23 kg
Dimensions	255 x 205 x 95 mm	164 x 72 x 72 mm
Supported languages	...	Polish, English, Chinese, Spanish, Korean, Italian, Turkish, Russian, Thai, French, Dutch, Hebrew, Arabic, Vietnamese, German, Ukrainian, Portuguese, Albanian
Manufacturer / Brand	ATTE	TIANDY
Guarantee	3 years	3 years