



	SD/MICRO SD MEMORY CARD READER Y-9321 UNITEK	IP SPEED DOME CAMERA OUTDOOR DS-2DE2A404IW-DE3/W(C0)(S6)(C) - 3.7 Mpx 2.8 ... 12 mm Hikvision
		
	13.62 EUR 13.62 EUR	383.62 EUR 383.62 EUR
Standard	...	TCP/IP
External connector	USB 3.1 - A plug	...
Sensor	...	1/2.8 " Progressive Scan CMOS
Matrix size	...	3.7 Mpx
Supported operating systems	Windows XP/Vista/7/8/8.1/10 (32/64bit), Linux, Mac OS 10.12 or newer	...
Transmission speed	≤ 5 Gb/s	...
Supported memory cards	SD (Secure Digital), microSD - SDHC, SDXC	...
Resolution	...	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens	...	2.8 ... 12 mm
Main features	<ul style="list-style-type: none"> • 1 x SD socket • 1 x microSD socket • Reading 2 memory cards simultaneously • Plug & Play 	...
View angle	...	<ul style="list-style-type: none"> • 97 ° ... 32 ° (manufacturer data) • 92 ° ... 31 ° (our tests result)
Optical zoom	...	x 4
Digital zoom	...	x 16
Range of IR illumination	...	20 m
Video output	...	—
Preset rotation speed	...	<ul style="list-style-type: none"> • 100 °/s (horizontal) • 100 °/s (vertical)
Rotation speed (manual control)	...	<ul style="list-style-type: none"> • 0.1 °/s ... 100 °/s (horizontal) • 0.1 °/s ... 100 °/s (vertical)
Horizontal rotation range	...	355 ° - Rotation of the head is limited by stops
Vertical rotation range	...	0 ° ... 90 °
RS-485 interface	...	—
Number of presets	...	300
Horizontal scan	...	—
Route settings	...	—
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—

Audio	...	<ul style="list-style-type: none"> • Microphone built-in • External microphone input • Audio output • Bi-directional audio streaming support • Audio detection
Main stream frame rate	...	25 fps @ 3.7 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	IPv4/IPv6, HTTP, HTTPS, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour, WebSocket, WebSockets
WEB Server	...	Built-in
Max. number of on-line users	...	20
ONVIF	...	✓
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default admin user / password	...	admin / - The administrator password should be set at the first start
Default IP address	...	192.168.1.64
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/- with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/- with authorization



Main features	...	<ul style="list-style-type: none"> • Built-in Wi-Fi module : IEEE 802.11 b/g/n, 300 Mbps (max) • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • NAS - Network Attached Storage support • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • ICR - Movable InfraRed filter • Privacy zones - max. 24 • Motion Detection • Sharpness - sharper image outlines • Mirror - Mirror image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • Intelligent image analysis : abandoned/missing object, crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, video tampering, face detection
Power supply	USB	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 760 mA
Power consumption	...	≤ 9.2 W @ 12 V DC
Housing	...	Speed Dome, Metal
Color	White	White + Black
"Index of Protection"	...	IP66
Vandal-proof	...	IK10
Operation temp	...	-20 °C ... 60 °C
Weight	0.02 kg	0.63 kg
Dimensions	<ul style="list-style-type: none"> • 38 x 35 x 11 mm • 12 cm (cable length) 	Ø 131 x 102 mm
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Turkish, Hungarian, Italian
Manufacturer / Brand	UNITEK	Hikvision
SAP Code	...	327000403
Guarantee	2 years	3 years