




	EXPANSION PLUG KW-10/5X70 KLIMAS	ANTENNA AMPLIFIER AFP-0160/18 18 dB	ACCESS CONTROLLER PR621 ROGER
			
	0.13 EUR 0.13 EUR	13.27 EUR 13.27 EUR	108.09 EUR 108.09 EUR
Relay contacts load	1.5 A / 30 V
Channels	...	3 - 69	...
Battery backup support	—
Keyboard built-in	—
Material	<ul style="list-style-type: none"> • Expansion plug, Polypropylene • Screw, Steel galvanized
Frequency range	...	76 MHz ... 860 MHz	...
Input lines	3
Drilling diameter	10 mm
Gain	...	18 dB	...
Output lines	3
Expansion plug length	50 mm
Number of inputs/outputs	...	1 / 1	...
Communication	<ul style="list-style-type: none"> • RS-485 • RACS (Roger)
IMA3 60dB	...	88 dB μ V	...
Screw dimensions	Ø 5 x 70 mm, PZ-2
Amplifier shield	...	✓	...
Input/output impedance	...	75 Ω	...
Connectors type	...	"F"	...
Application	<ul style="list-style-type: none"> • Concrete • Solid clay brick • Solid sand-lime brick
Housing	...	Plastic	...
Mounting	...	on a mast or a wall	...
Power supply	...	12 V / 50 mA via antenna cable	10 ... 15 V DC

Main features	<ul style="list-style-type: none"> • Unique EM 125kHz proximity reader built-in • PRT series readers support • 1000 indexed users • History of 250 000 events • 99 General Purpose Schedules • 250 access groups • Tamper detection - removing from mounting surface • Function to prevent of multiple use of the same code/card to gain access (anti-passback)
Environment class	IV
Operation temp	-25 °C ... 60 °C
Permissible relative humidity	10 ... 95 % (non-condensing)
Weight	0.15 kg
Dimensions	85 x 85 x 27 mm
Manufacturer / Brand	KLIMAS	DELTA	ROGER
Guarantee	2 years	3 years	3 years