




	AHD, HD-CVI, HD-TVI, PAL CAMERA APTI-H52C21-36W - 8.3 Mpx, 4K UHD 3.6 mm	DC FILTER FDC-08 TO SWITCHING ADAPTERS	POLE MOUNT A36_V5.0 TIANDY
			
	32.66 EUR 32.66 EUR	9.60 EUR 9.60 EUR	38.18 EUR 38.18 EUR
Suitable for cameras	Tiandy - documentation for download below.
Maximal current	...	0.8 A	...
Power connectors type	...	2.1/5/5 mm plug	...
Housing type	...	2.1/5.5 mm socket	...
Standard	AHD, HD-CVI, HD-TVI, PAL
Pole diameters range	Ø 60 ... Ø 135 mm
Material	Metal
Sensor	1/2.5 " Progressive Scan CMOS
Matrix size	8.3 Mpx
Resolution	3840 x 2160 - 8.3 Mpx, 4K UHD @ AHD / HD-CVI / HD-TVI, 15 fps , 3840 x 2160 - 8.3 Mpx, 4K UHD @ HD-CVI / HD-TVI, 12.5 fps , 2592 x 1944 - 5 Mpx @ AHD / HD-TVI, 20 fps, 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI, 30 fps, 25 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI, 15 fps , 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI, 30 fps, 25 fps , 960 x 576 - 960H @ CVBS
Lens	3.6 mm
View angle	• 77 ° (manufacturer data) • 83 ° (our tests result)
Range of IR illumination	25 m
IR illuminator power adjustment	Automatic
Video output	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI / PAL - selectable by switch, Via OSD
Audio	—
OSD menu	✓

Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • ICR - Movable InfraRed filter • DNR - Digital Noise Reduction • AGC - Automatic Gain Control • BLC - Back Light Compensation • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines
Power supply	12 V DC / 220 mA
Power consumption	≤ 2.7 W
Housing	Compact - Metal Plastic
Color	White	...	White
"Index of Protection"	IP67
Operation temp	-20 °C ... 50 °C
Weight	0.24 kg	0.02 kg	0.69 kg
Dimensions	178 x 72 x 72 mm	26 x 21 x 16 mm	137 x 165 mm
Supported languages	Polish, English, French, Spanish, Portuguese, Russian, Italian
Manufacturer / Brand	APTI	DELTA	TIANDY
Guarantee	2 years	3 years	3 years