

	AHD, HD-CVI, HD-TVI CAMERA APTI-H51V2-28 2Mpx / 5Mpx 2.8 mm	OPTICAL ANTI FOAM DETECTOR SX6-TO SATEL
		
	29.13 CHF 29.13 CHF	9.57 CHF 9.57 CHF
Detection	...	Foaming
Alarm signaling	...	LED indicator, Signal to control panel
Standard	AHD, HD-CVI, HD-TVI	...
Sensor	1/3 " Progressive Scan CMOS	...
Application	...	SD-6000
Matrix size	5 Mpx	...
Operation temp	...	-25 °C ... 55 °C
Resolution	2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI @ 30 fps, 25 fps, 15 fps , 2560 x 1440 - 4 Mpx @ HD-CVI @ 30 fps, 25 fps , 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 30 fps, 25 fps	...
Range of IR illumination	20 m	...
IR illuminator power adjustment	Automatic	...
Lens	2.8 mm	...
View angle	• 89 ° (manufacturer data) • 83 ° (our tests result)	...
Video output	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch	...
OSD menu	✓	...

Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines • Coaxial audio - HD-TVI only 	...
Housing	Dome - Metal	...
Color	Graphite	...
Vandal-proof	—	...
"Index of Protection"	IP67	...
Power supply	12 V DC / 230 mA	12 V DC / 45 mA
Power consumption	≤ 2.8 W	...
Operation temp	-20 °C ... 60 °C	...
Weight	0.42 kg	0.012 kg
Dimensions	Ø 96 x 91 mm	98 x 54 mm
Supported languages	Polish, English	...
Manufacturer / Brand	APTI	SATEL
Guarantee	2 years	2 years