





	<a href="#">ACCESS POINT MAP-2ND mAP, 2.4 GHz 300 Mbps MIKROTIK</a>	<a href="#">ACCESS POINT NANOSTATION-M2 UBIQUITI</a>	<a href="#">ACCESS POINT LOCO-M2 UBIQUITI</a>	<a href="#">INDOOR PANEL VTH2611L- WP Wi-Fi / IP DAHUA</a>
				
	20064.76 HUF 20064.76 HUF	43343.81 HUF 43343.81 HUF	24243.81 HUF 24243.81 HUF	48761.90 HUF 48761.90 HUF
Compatibility	...	...	...	DAHUA
Frequency range	2.4 GHz	2412 MHz ... 2462 MHz	2412 MHz ... 2462 MHz	...
Shield	...	...	...	4.3 " capacitive touch screen
Resolution	...	...	...	480 x 272
Polarization	...	vertical/horizontal	vertical/horizontal	...
Internal memory	...	...	...	—
Memory card slot	...	...	...	—
Antenna type	2 x 2 MIMO Omnidirectional antenna , Dual-chain - embedded 1.2 dBi	2Tx 2Rx MIMO 11 dBi Integrated	2Tx 2Rx MIMO 8 dBi Integrated	...
Standards	IEEE 802.11 b/g/n	<ul style="list-style-type: none"> <li>• IEEE 802.11b</li> <li>• IEEE 802.11g</li> <li>• IEEE 802.11n</li> </ul>	<ul style="list-style-type: none"> <li>• IEEE 802.11b</li> <li>• IEEE 802.11g</li> <li>• IEEE 802.11n</li> </ul>	...
Baud rates	300 Mbps	...	...	...
VSWR	...	1.6 : 1	1.4 : 1	...
LAN ports	2 x 10 / 100 Mbps LAN	2 x 10/100 Mbps BASE-TX (Cat. 5, RJ-45)	1 x 10/100 Mbps	...
LED indicators	Power, Operation mode, WiFi, User, PoE OUT, 2 x Ethernet	...	...	...
Main features	...	...	...	<ul style="list-style-type: none"> <li>• Wi-Fi Module - 2.4 GHz IEEE 802.11 b/g/n,</li> <li>• IP Dahua cameras support,</li> <li>• Microphone built-in,</li> <li>• Speaker built-in,</li> <li>• Bidirectional communication,</li> <li>• Echo suppression and reduction / digital noise reduction,</li> <li>• Receive and view the published information from the management center,</li> <li>• DND mode ,</li> </ul>
Controlling	...	...	...	capacitive touch screen
Alarm inputs	...	...	...	4
Protections	...	15kV surge protection of radio line	15kV surge protection of radio line	...
Alarm outputs	...	...	...	1

Receiver sensitivity	2.4 GHz : • 1M : -96 dBm • 11M : -89 dBm • 6M : -93 dBm • 54M : -74 dBm • MCS0 : -93 dBm • MCS7 : -71 dBm	• -83 dBm @ 1 ... 24 Mbps • -80 dBm @ 36 Mbps • -77 dBm @ 48 Mbps • -75 dBm @ 54 Mbps	• -83 dBm @ 1 ... 24 Mbps • -80 dBm @ 36 Mbps • -77 dBm @ 48 Mbps • -75 dBm @ 54 Mbps	...
DHCP server	✓	...	...	...
Firmware update	✓	...	...	...
Transmitter power	max. 22 dBm	• 28 dBm @ 1 ... 24 Mbps • 26 dBm @ 36 Mbps • 25 dBm @ 48 Mbps • 24 dBm @ 54 Mbps	• 23 dBm @ 1 ... 24 Mbps • 21 dBm @ 36 Mbps • 19 dBm @ 48 Mbps • 18 dBm @ 54 Mbps	...
Horizontal beam width (H)	...	55 °	60 °	...
Color	...	...	...	White
Operating system	MikroTik RouterOS	AirOS	AirOS	...
Vertical beam width (V)	...	53 °	60 °	...
Management interface	Web browser, MikroTik application	...	...	...
Memory	...	32 MB SDRAM, 8 MB FLASH	32 MB SDRAM, 8 MB FLASH	...
Default IP address	192.168.88.1	...	...	...
Processor	Qualcomm Atheros AR9531 650 MHz	Atheros MIPS 24KC, 400MHz	Atheros MIPS 24KC, 400MHz	...
Power supply PoE	...	✓	✓	...
Supported languages	...	...	...	Polish, English
Operation modes	• Access Point, • Station	Station, Station WDS, Access Point, Access Point WDS	Station, Station WDS, Access Point, AccessPoint WDS	...
Permissible relative humidity	...	5 % ... 95 %	5 % ... 95 %	...
Power supply	• 8 ... 57 V DC - 24 V DC / 0.8 A (power adapter included) • 10 ... 57 V DC - Passive PoE, PoE (802.3af/at) • 5 V DC - Micro USB-B socket	24 V / 0.5 A (power adapter included)	24 V / 0.5 A	• PoE (802.3af/at), • 12 V DC / 1 A
Power consumption	max. 5 W	...	...	• ≤ 6 W (operation) • ≤ 4 W (standby)

Main features	<ul style="list-style-type: none"> <li>• Dual-chain</li> <li>• MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network</li> <li>• Built-in 2-port switch</li> <li>• MDI/MDI-X auto detection feature - auto detecting the data transmission mode</li> <li>• Port USB 2.0 - Possibility to connect 3G/4G modem, Power connector</li> <li>• PoE IN : PoE 802.3af/at / PASSIVE - port ETH1</li> <li>• PoE OUT : Passive PoE - port ETH2</li> <li>• Voltage control</li> <li>• Mode button</li> <li>• RESET button</li> <li>• USB A / micro USB B cable included</li> </ul>	...	...	...
Operation temp	-20 °C ... 70 °C	-30 °C ... 75 °C	-30 °C ... 80 °C	-10 °C ... 55 °C
Weight	0.068 kg	0.4 kg	0.190 kg	0.2 kg
Dimensions	68 x 68 x 19 mm	278 x 80 x 59 mm	179 x 80 x 60 mm	140 x 136 x 26 mm
Manufacturer / Brand	MikroTik	UBIQUITI	UBIQUITI	DAHUA
Guarantee	2 years	2 years	2 years	3 years

