




	ELECTRICAL INSTALLATION CONNECTION KZ-37	NVR NVR302-09S 9 CHANNELS UNIVIEW
		
	0.76 AUD 0.76 AUD	369.55 AUD 369.55 AUD
Inner diameter	Ø 37 mm	...
Standard	...	TCP/IP
Main features	The corrugation of the connection enables its bend	...
Pipe mounting method	Pressing	...
Supported resolutions	...	max. 8.3 Mpx 4K UHD - 3840 x 2160 px
Color	White	...
Video outputs	...	1 pcs HDMI 4K 1 pcs VGA
Audio support	...	<ul style="list-style-type: none"> • 9 Channels - Audio from cameras • Bi-directional audio streaming support
Audio inputs	...	1 pcs CINCH
Audio outputs	...	1 pcs CINCH
Image compression method	...	Ultra 265 / H.265 / H.264
Bitrate	...	max. 160 Mbps
Supported hard drives	...	2 x 8 TB SATA
Recording modes	...	Manual, Motion Detection, Schedule
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) Records playback from max. 9 channels in the same time
Network interface	...	1 x RJ-45 10/100/1000 Base-TX
Network functions	...	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users
Network protocols	...	P2P, UPnP, NTP, DHCP, PPPoE
ONVIF	...	✓
Default IP address	...	DHCP or 192.168.1.30
Default admin user / password	...	admin / 123456

Mobile phones support	...	Port no.: 80 or access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	...	80
RTSP URL	...	rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream
USB	...	1 x USB 2.0 1 x USB 3.0
Serial ports	...	—
Alarm inputs / outputs	...	—
PTZ control	...	PTZ Uniview cameras
Motion Detection	...	✓
Intelligent image analysis	...	✓
Main features	...	Functions implemented in cooperation between the recorder and cameras that support these functions • Intelligent image analysis : crossing the line (tripwire), intrusion, scene changing, objects tracking, people counting • Audio detection • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • Support ANR function
Mouse support	...	✓
IR remote controller in the set	...	—
Power supply	...	12 V DC / 2 A (power adapter included)
Power consumption	...	max. 7 W (without HDD)
Operation temp	...	-10 °C ... 55 °C
Weight	...	1.68 kg
Dimensions	Ø 40 x 180 mm	380 x 322 x 53 mm
Supported languages	...	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian
Manufacturer / Brand	...	UNIVIEW

Guarantee	2 years	3 years
-----------	---------	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00