





	<a href="#">TV OR MONITOR MOUNT BRATECK-FS22-44TP</a>	<a href="#">SWITCHING ADAPTER 12V/1.67A-TP-V2 MW POWER</a>	<a href="#">UPS UPS06_600 VA Green Cell</a>	<a href="#">ROUTER ARCHER-C50 2.4 GHz, 5 GHz 300 Mbps + 867 Mbps TP-LINK</a>
				
	44.97 EUR 44.97 EUR	4.63 EUR 4.63 EUR	74.35 EUR 74.35 EUR	34.86 EUR 34.86 EUR
Power adapter type	...	...	Line-interactive	...
Adapter type	...	Switching	...	...
Nominal power	...	...	360 W	...
Apparent Power	...	...	600 VA	...
Antenna type	...	...	...	4 x Omnidirectional antenna
Power voltage	...	100 ... 240 V AC	...	...
Input voltage	...	...	162 V ... 290 V AC	...
Frequency range	...	50 / 60 Hz	...	2.4 GHz, 5 GHz
Input frequency	...	...	50 / 60 Hz (auto detection)	...
Standards	...	...	...	IEEE 802.11 b/g/n @ 2.4 GHz IEEE 802.11 a/n/ac @ 5 GHz
Output voltage tolerance	...	± 0.5 V	...	...
Maximal load	...	1.67 A	...	...
Baud rates	...	...	...	300 Mbps + 867 Mbps
Output power	...	20 W	...	...
Mounting standard	VESA : 100 x 100, 200 x 100, 200 x 200, 300 x 200, 300 x 300, 400 x 200 400 x 300, 400 x 400	...	...	...
Screen size range	32 " ... 55 "	...	...	...
Output voltage	...	12 V DC	• 230 V AC ± 10 % (Approximated Sine Wave) • 5 V DC - USB Charger	...
Bearing capacity	35 kg	...	...	...
LAN ports	...	...	...	4 x 10/100 Mbps LAN 1 x 10/100 Mbps Uplink
Color	Black	...	...	...
Output frequency	...	...	50 / 60 Hz ± 1 Hz	...
Tilt adjustment	-10 ° ... 10 °	...	...	...
Horizontal rotation	—	...	...	...
Rotation in the plane of the screen	—	...	...	...
Transfer time	...	...	2 ... 6 ms (typical), max. 10 ms	...
"Index of Protection"	...	IP67	...	...
LED indicators	...	...	...	Power, 2.4 GHz WLAN, 5 GHz WLAN, Ethernet, WAN, WPS
Charging time (recover to 90% capacity)	...	...	6 ... 8 hours	...

Battery	...	...	1 pcs - 12V/7Ah	...
Estimated battery operation time	...	...	≤ 20 minutes - depending on the load	...
Number of outputs	...	1 pcs	<ul style="list-style-type: none"> <li>• 6 pcs CEE 7/3 (Schuko),</li> <li>• 1 pcs USB-A - 5 V / 1 A</li> </ul>	...
Receiver sensitivity	...	...	...	2.4 GHz : <ul style="list-style-type: none"> <li>• 11g 54M : -76 dBm</li> <li>• 11n HT20 MCS7 : -74 dBm</li> <li>• 11n HT40 MCS7 : -71 dBm</li> </ul> 5 GHz : <ul style="list-style-type: none"> <li>• 11a 54M : -77 dBm</li> <li>• 11ac VHT20 MCS8 : -72 dBm</li> <li>• 11ac VHT40 MCS9 : -68 dBm</li> <li>• 11ac VHT80 MCS9 : -63 dBm</li> </ul>
DDNS	...	...	...	✓
DHCP server	...	...	...	✓
Firmware update	...	...	...	✓
Protections	...	...	<ul style="list-style-type: none"> <li>• Short-circuit</li> <li>• Overvoltage</li> <li>• Overload</li> <li>• Overcharge</li> <li>• Discharge</li> <li>• Overheat</li> <li>• Ethernet filter - RJ-45</li> </ul>	WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK DoS attacks protection, SPI network firewall, domain filtering, IP and MAC filtering, IP and MAC binding
Management interface	...	...	...	Web browser, TP-LINK Tether
Operation state indication	...	...	<ul style="list-style-type: none"> <li>• LCD display: operation mode, battery charging level, in/out voltage level, Work load, Overload signaling, Failure signaling, Low battery level alarm,</li> <li>• Sound signaling</li> </ul>	...
Power supply	...	...	...	9 V DC / 0.85 A (power adapter included)



Main features	Adjustable shelf height in the range of 60 cm	Can be installed in a 60mm electrical box	<ul style="list-style-type: none"> <li>• Microprocessor control system</li> <li>• UPS auto diagnostic system</li> <li>• Automatic Voltage Regulator (AVR)</li> <li>• Auto restart while AC is recovering</li> <li>• "Cold Start" function</li> <li>• Battery charging at power-off mode</li> <li>• Fast intelligent battery recharge function</li> <li>• Remote management - GC UPS application ( Display of operating parameters, schedule, e-mail personal messaging, local access )</li> <li>• USB interface</li> <li>• USB Charger,</li> <li>• USB A / USB B cable included + 2 x Power supply cable</li> <li>• The ergonomic shape - power outlets located on the top of the housing</li> </ul>	<ul style="list-style-type: none"> <li>• Firewall</li> <li>• Internet access filtering</li> <li>• Static / dynamic routing</li> <li>• Built-in 4-port switch</li> <li>• Wireless transmission statistics</li> <li>• The WPS function allows to easy establish an encrypted connection</li> <li>• QoS</li> <li>• WMM (Wi-Fi Multimedia)</li> <li>• Rate limit</li> <li>• Access control</li> <li>• Remote management</li> <li>• DMZ</li> <li>• parental control</li> <li>• Guest Network - a separate and secure network for guests</li> <li>• SSID hiding</li> </ul>
Operation temp	...	-20 °C ... 50 °C	...	0 °C ... 40 °C
Permissible relative humidity	...	...	...	10 % ... 90 % (non-condensing)
Application	...	...	<ul style="list-style-type: none"> <li>• Surveillance Systems</li> <li>• data storage centers</li> <li>• network, servers, workstations</li> <li>• Industrial Equipment</li> </ul>	...
Housing type	...	Plastic	Desktop, Possibility to mount to the wall	...
Operation temp. / Relative humidity	...	...	0 °C ... 40 °C / 0 ... 90 %	...
Weight	12 kg	0.08 kg	4.5 kg	0.30 kg
Dimensions	1170 ... 1470 x 600 x 400 mm	Ø 50 x 23 mm	290 x 200 x 92 mm	230 x 145 x 34 mm
Manufacturer / Brand	BRATECK	MW POWER	Green Cell	TP-LINK
Guarantee	2 years	2 years	2 years ( 12 months - battery )	3 years