

	WIRELESS PIR DETECTOR ARD1233-W2(868) DAHUA	POE SWITCH, EXTENDER XPOE-4-11A-HS 4-PORT ATTE
		
	59.83 GBP 59.83 GBP	37.65 GBP 37.65 GBP
Support	Wireless alarm systems DAHUA	...
Application	Indoor	...
Pyroelectric sensor	Double, Low Noise Ratio	...
Sensor type	Passive Infra Red (PIR)	...
LAN ports	...	<ul style="list-style-type: none"> • 1 x LAN + PoE IN - Port LAN 1, • 3 x LAN + PoE OUT - LAN2 ... LAN4 ports
Frequency range	868.0 ... 868.6 MHz	...
Radio communication range (at open area)	max. 1600 m	...
Recommended installation height	2.2 m	...
Management	...	—
Detection range / Detection angle	12 m / 90 °	...
LED diodes	...	Power, LAN
Sensitivity adjustment	max. 3 levels	...
Transmission speed	...	10 / 100 Mbps
Pet immunity	≤ 18 kg	...
Digital temperature compensation	✓	...
Alarm output	Wireless	...
Target speed range	0.3 ... 3 m/s	...
Maximal output power	...	<ul style="list-style-type: none"> • 40 W @ Passive PoE - LAN2 ... LAN4 ports • 13 W / 25 W @ PoE (802.3af/at) - LAN2 ... LAN4 ports

Main features	<ul style="list-style-type: none"> • Tamper protections • Low battery level alarm • Frequency hopping against jamming for reliable transmission • AES128 data encryption • Measurement of signal strength and quality • Test mode • Temperature measurement in the range: -15°C ... +65°C • Remote update of software • LED indicator • ON/OFF button 	<ul style="list-style-type: none"> • Possibility to power up to 3 PoE 802.3at/af or PASSIVE receivers • Possibility to connecting in cascade • The ability to turn off the power on selected PoE ports • The output PoE voltage is equal to the input voltage • Overvoltage protection • Short-circuit protection - LAN 1
Environment class	II	...
Protection class (Grade)	Grade 2	...
Compliance with standards	EN50131-1:2006+A2:2017+A3:2020, EN 50131-2-2:2017, EN 50131-6:2017, EN 50131-5-3:2017	...
Housing	Plastic (PC + ABS)	...
Power supply	...	<ul style="list-style-type: none"> • 44 ... 56 V DC - LAN 1, • 12 ... 56 V DC - LAN 2 ... LAN 4
Color	White	...
Battery	1 x CR123A 3 V (included)	...
Backup time	~ 4 years	...
Current consumption	max. 120 mA	...
Operation temp	-10 °C ... 55 °C	...
Weight	0.106 kg	0.04 kg
Dimensions	60 x 104 x 51 mm	94 x 41 x 18 mm
Manufacturer / Brand	DAHUA	ATTE
Guarantee	3 years	3 years