

	CONVERTER TO COMPUTER MONITORS VGA-1920F	ALLEN SCREW SI- M8X35/KL-8.8	ALLEN SCREW SI- M8X30/KL-8.8
			
	24.97 EUR 24.97 EUR	0.20 EUR 0.20 EUR	0.20 EUR 0.20 EUR
Size	...	M8	M8
Material	...	Steel galvanized	Steel galvanized
Strength class	...	8.8	8.8
Main features	...	DIN 912 compliance	DIN 912 compliance
Input	<ul style="list-style-type: none"> • Video composite (BNC socket), • S-VIDEO, • VGA (bypass)
Wrench size	...	6 mm	6 mm
Thread length	...	35 mm	30 mm
Input signal possible standards	<ul style="list-style-type: none"> • PAL, NTSC, • VGA (bypass)
Output	VGA (bypass)
Supported resolutions	<ul style="list-style-type: none"> • 4:3 800 x 600 @ 60/75 Hz 1024 x 768 @ 60 Hz 1280 x 1024 @ 60 Hz 1600 x 1200 @ 60 Hz • 16:9 / 16:10 1280 x 720 @ 60 Hz 1366 x 768 @ 60 Hz 1440 x 900 @ 60 Hz 1680 x 1050 @ 60 Hz 1920 x 1080 @ 60 Hz 1920 x 1200 @ 60 Hz
OSD menu	✓
Possible settings	<ul style="list-style-type: none"> • brightness, contrast, saturation, hue - the settings are saved after power off • PIP - Picture In Picture
Power supply	5 V / 1 A (power adapter included)
Weight	0.07 kg	0.017 kg	0.016 kg
Dimensions	100 x 65 x 26 mm	Ø 12.8 x 42.8 mm	Ø 12.8 x 38.3 mm
Guarantee	2 years	2 years	2 years