





	SMART GATE AND DOOR CONTROLLER GATEBOX-PRO/BLEBOX Wi-Fi, 12 ... 24 V DC/AC	FINAL SOCKET RJ45-2G1/6 DOUBLE	LIVE WIRE, METAL AND WOOD DETECTOR UT-387E UNIT	EXTENDER HDMI-EX-6IR
				
	56.11 EUR 56.11 EUR	2.51 EUR 2.51 EUR	41.43 EUR 41.43 EUR	53.85 EUR 53.85 EUR
Mount	...	Surface-mounted
Application	swing gates, sliding gates, garage gates, doors
Material	...	PET
Rated voltage	12 ... 24 V DC/AC
Application	...	RJ-45
Maximal total load	—
Total maximal current	20 mA / Control output
Number of inputs	2
Supported HDMI resolutions	1080i - 50/60 Hz, 720p, 576p, 576i, 480p, 480i
Number of outputs	2	2
Connector type	screw terminals
Detector range	<ul style="list-style-type: none"> • Wood : 38 mm, • Non-ferromagnetic metal : 80 mm, • Ferromagnetic metal : 100 mm, • AC live wires : 40 mm 	...
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g
Maximal transmission range	<ul style="list-style-type: none"> • 45 m @ 720p / 1080i - UTP cat. 5 • 60 m @ 720p / 1080i - UTP cat. 6
Mobile phones support	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS
Supported audio formats	DTS-HD, Dolby true HD, LPCM7.1, AC3, DTS, DSD
Power supply	Built-in 3.7V / 300mAh battery, charging via USB-C connector	5 V DC / 1000 mA - 2 pcs of power adapters included

Main features	<ul style="list-style-type: none"> • Control of the electric strike and automatic gate, • Multiple users support from anywhere, • Control many objects from one app, • remote access, • voice control, • Omnidirectional antenna 	<ul style="list-style-type: none"> • It is compatible with Category 6 • Twisted-pair cable mounting using the Krone Impact Tool 	<ul style="list-style-type: none"> • Automatic calibration after turned on, • Optical - sound signaling, • Large, easy to read LCD graphic display with backlight, • ZOOM function - More precise location of small metal elements with visualization of their location 	IR receiver : 20 ... 60 kHz
Permissible relative humidity	5 % ... 90 %
Housing	Plastic, Waterproof, Weatherproof
"Index of Protection"	IP54
Color	Black	White
Operation temp	-20 °C ... 50 °C	-10 °C ... 55 °C
Weight	0.1 kg	0.046 kg	0.15 kg	0.08 kg
Dimensions	<ul style="list-style-type: none"> • 92 x 50 x 28 mm - without antenna • 230 x 85 x 28 mm - with antenna, vertical • 197 mm - Antenna 	62 x 60 x 26 mm	148 x 68 x 30 mm	72 x 67 x 25 mm
Manufacturer / Brand	BleBox	...	UNI-T	...
Guarantee	2 years	3 years	2 years	2 years