



	NVR TC-R3108 SPEC:I/B/P8/C/EU/L/S 8 CHANNELS, 8 PoE TIANDY	ELECTRIC CABLE DY-2.5-RD/750V
		
	126.95 EUR 126.95 EUR	0.43 EUR 0.43 EUR
Standard	IP	...
Supported resolutions	max. 6 Mpx	...
Video outputs	1 pcs HDMI	...
In section	...	100 m . Price for 1m when buying a whole roll
Audio support	8 Channels - Audio from cameras	...
Inner conductor	...	2.5 mm ² - Cu wire
Audio inputs	—	...
Rated voltage	...	450 / 750 V
Audio outputs	—	...
Outer coating	...	Ø 3.3 mm - PVC
Coating color	...	Red
Image compression method	S+265 / H.265 / S+264 / H.264	...
Supported hard drives	1 x 6 TB SATA	...
Recording modes	Manual, Motion Detection, Schedule	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4 channel synchronous playback	...
Network interface	1 x RJ-45 - 10 / 100 Mbps	...
Network functions	Full support via network, Remote records copying, Web-Server built-in	...
ONVIF	✓	...
Bitrate	max. 60 Mbps	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Default IP address	192.168.1.3	...
RTSP URL	rtsp://user:password@192.168.1.3:554/1/1 - Main stream rtsp://user:password@192.168.1.3:554/1/2 - Sub stream	...

Web browser access ports	80, 443, 3000, 3001, 3002, 23002	...
PC client access ports	3000, 3001	...
Mobile client access ports	3000, 3001	...
Mobile phones support	Port no.: 3000 or access by a cloud (P2P) • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus	...
Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express	...
Alarm inputs / outputs	—	...
Motion Detection	✓	...
Intelligent image analysis	—	...
USB	2 x USB 2.0	...
Mouse support	✓	...
IR remote controller in the set	—	...
Main features	—	...
Switch PoE	8-port PoE Switch built-in, 30 W / Channel - PoE	...
Maximum total switch load	45 W	...
Power supply	48 V DC / 1.35 A (power adapter included)	...
Weight	0.45 kg	...
Dimensions	201 x 201 x 43 mm	...
Supported languages	English, Spanish, Italian, French, Dutch, German, Portuguese	...
Manufacturer / Brand	TIANDY	...
Guarantee	3 years	2 years