




	SWITCH DS-KAD7061EY FOR HIKVISION 2-WIRE VIDEO DOORPHONE SYSTEMS	CHARGER BAT-RECHARGE/VC2SL XTAR	KRONE BACK-MOUNT FRAME LSA-GN-10/5
			
	50.46 USD 50.46 USD	18.82 USD 18.82 USD	3.94 USD 3.94 USD
Number of mounted profile modules	5 pcs
Type of mounted profile modules	10PAR
Number of ports	4 x HIKVISION 2-wire (Total max. 20 W) , 2 x HIKVISION 2-wire - Uplink
Compatibility	HIKVISION 2-wire - EY series
Power consumption	< 2 W
Housing	Plastic
Operation temp	-10 °C ... 55 °C
SAP Code	305304457
Battery type	...	<ul style="list-style-type: none"> • Li-Ion 3.6 / 3.7 V - ICR / IMR / INR : 10440, 14500, 14650, 16340, 16650, 17335, 17500, 17670, 18350, 18490, 18500, 18505, 18650, 18700, 20700, 21700, 22650, 25500, 26650, • Ni-MH, Ni-Cd 1.2 V - AAAA / AAA / AA / A / C 	...
Battery charging current	...	0.5 A @ 2 pcs , 1 A @ 2 pcs , 2 A @ 1 pcs	...
LED indicator	...	—	...
LCD display	...	✓	...

Main features	Possibility to connecting in cascade	<ul style="list-style-type: none"> • The LCD display informs about the charging capacity, cell voltage, charging current and internal resistance of the cell, • Supports protected PCM/PCB batteries in sizes 20700/21700, • Deeply discharged cell reactivation function, • Power Bank (5V, max. 1A) function • Charging Li-ion batteries controlled by a three-stage processor TC/CC/CV charging process • charging Ni-MH batteries with the CC method • 2 independent charging channels • End of charge voltage : 4.2 V @ Li-Ion, 1.45 V @ NiMH • Short-circuit protection • Protection against reverse polarity connection • Thermal protection • USB-C / USB-A cable included 	...
Power supply	48 V DC - From the master switch DS-KAD7060EY	5 V DC / 2 A @ USB-C socket (power adapter not included)	...
Weight	0.08 kg	0.11 kg	...
Dimensions	71 x 60 x 25 mm	<ul style="list-style-type: none"> • 68 x 137 x 34 mm • 80 cm (cable length) 	112 x 112 x 50 mm
Manufacturer / Brand	Hikvision	XTAR	...
Guarantee	3 years	2 years	2 years