



	SHACKLE SZEKLA-5MM	ACCESS CONTROL PANEL ACCO-NT2 SATEL	SINGLE FURNITURE SOCKET OUTLET WITH USB POWER ADAPTER OR-AE-13124/B 230 V AC 16 A ORNO
			
	0.55 EUR 0.55 EUR	372.58 EUR 372.58 EUR	33.79 EUR 33.79 EUR
Application	Steel lines
Material	Metal
Rated voltage	230 V AC / 50 Hz
Maximal current load	16 A
Maximal total load	3680 W
Inputs	...	<ul style="list-style-type: none"> • 8 pcs - Mainboard inputs • max. 264 	...
Grounding	✓
Power supply USB	5 V DC / 2.4 A
Electrical cable	3 x 1 mm ²
Outputs	...	<ul style="list-style-type: none"> • 8 pcs - Mainboard inputs • max. 264 	...
Number of outlets	<ul style="list-style-type: none"> • 1 pcs 230 V AC • 1 pcs USB
Communication	...	<ul style="list-style-type: none"> • 2 x RS-485 • Expander bus - up to 32 expander modules 	...
Socket type	<ul style="list-style-type: none"> • E type CEE 7/5, • USB-A
Protection shutter	✓
Events memory	...	<ul style="list-style-type: none"> • Events saving to the micro SD card (included) • Recording up to 1 000 000 events from the control panel, • Max. 100 000 events read from each access control module 	...
Assembly	Fixing in the opening of the table top Ø 60 mm
Users + admins	...	<ul style="list-style-type: none"> • 8000 + 1 • Max. 65 000 users in the whole ACCO NET system 	...
Housing	Plastic
Color	Black
Output load	...	<ul style="list-style-type: none"> • OC : 50 mA / 12 V DC • +EX : 0.5 A / 12 V DC • AUX : 0.5 A / 12 V DC 	...

Main features	<ul style="list-style-type: none"> • U-shaped metal bar diameter 5 mm • Work load 100 kg • Corrosion resistance 	<ul style="list-style-type: none"> • Support for up to 255 access control modules • Ability to create up to 255 partitions in 1 control panel (up to 255 access control modules can be defined in one partition) • Ability to add up to 16 passageways (up to 16 partitions can be defined in each passageway) • Ability to block/unblock partition at a specified time, or as per access schedule, • Ability to assign 4 identifiers and a keyfob to a single user, • Ability to assign up to 4 proximity cards / DALLAS chips (iButtons) to a user, • Up to 256 access calendars, weekly schedules, daily schedules, time frames • Ability to control the control panel outputs by using keyfobs • Implementation of logic functions on inputs and outputs • Support for turnstiles • Electrical protection of all inputs and outputs as well as communication buses 	<ul style="list-style-type: none"> • Sliding cover • Flat plug • mounting depth max. 80 mm
Power supply	...	12 V DC / 140 mA (max)	...
Battery backup support	...	—	...
Operation temp	...	-10 °C ... 55 °C	...
Permissible relative humidity	...	93 % (non-condensing)	...
Weight	0.015 kg	0.096 kg	0.37 kg
Dimensions	30 x 30 x 10 mm	151 x 69 x 17 mm	<ul style="list-style-type: none"> • 100 x 70 x 90 mm • 1.9 m - Length of the cable
Manufacturer / Brand	...	SATEL	ORNO
Guarantee	2 years	2 years	2 years