



	HD-CVI, PAL, TCP/IP DVR DHI-HCVR5208A-S2 8 CHANNELS DAHUA	STRAIGHT PLUG LE-50110 230 V 16 A LEGRAND
		
	4575.99 NOK 4575.99 NOK	98.24 NOK 98.24 NOK
Rated voltage	...	230 V / 50 Hz
Standard	HD-CVI, PAL, TCP/IP	...
Maximal current load	...	16 A
Grounding	...	✓
Electrical cable	...	max. 3 x 2.5 mm ²
Cable terminals	...	automatic spring terminals
Plug type	...	CEE 7/6
"Index of Protection"	...	IP44
Mechanical strength	...	IK08
Color	...	Black
Maximal total frame rate	<ul style="list-style-type: none"> • HD-CVI, PAL : 120 fps @ 1920 x 1080 px, 200 fps @ 1280 x 720 px, 200 fps @ 960 x 576 px, • IP : 50 fps @ 1080p 	...
Recording speed adjustment	<ul style="list-style-type: none"> • HD-CVI, PAL 1 ... 15 fps @ 1920 x 1080 1 ... 25 fps @ 1280 x 720 1 ... 25 fps @ 960 x 576 • IP 1 ... 25 fps @ 1920 x 1080 	...
Supported resolutions	8 x HD-CVI @ 1080p / Composite Video (CVBS) @ 960H 6 x HD-CVI @ 1080p / Composite Video (CVBS) @ 960H + 2 x IP @ 1080p	...
Video inputs	8 pcs BNC - HD-CVI / Composite Video (CVBS)	...
Video outputs	1 pcs HDMI 1 pcs VGA	...
Audio inputs	4 pcs CINCH	...
Audio outputs	1 pcs CINCH	...
Image compression method	H.264	...
Number of compression levels	5	...

Image records resolutions	1920 x 1080 1280 x 720 960 x 576 704 x 576 352 x 288 176 x 144	...
Recording modes	Manual, Sensor, Motion detection, Schedule	...
Supported hard drives	2 x 8 TB SATA	...
External storage devices backup	Save single frames and whole records from DVR drive to the USB drive	...
Searching and playback the records	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy)	...
Network functions	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters - DSS/Smart PSS application	...
Network protocols	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P	...
Bitrate	max. 32 Mbps (total)	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS There are also paid versions of mobile applications: gDMSS Plus, iDMSS Plus, wDMSS plus	...
Alarm inputs / outputs	8 / 3	...
PTZ control	RS-485 Many protocols	...

Motion Detection	Split the screen into zones 22 x 18 motion zones Very good sensitivity, after motion detection records detected channels only	...
Mouse support	✓	...
IR remote controller in the set	—	...
Power supply	12 V DC / 4 A (power adapter included)	...
Weight	2.35 kg	0.058 kg
Dimensions	375 x 285 x 55 mm	122 x 43 x 42 mm
Supported languages	English	...
Country of origin	China	...
Manufacturer / Brand	DAHUA	LEGRAND
Guarantee	3 years	2 years