



	MONITOR DESK MOUNT AX-PIXEL-SINGLE RED EAGLE	NVR APTI-N3228AI-13 32 CHANNELS
		
	18.09 EUR 18.09 EUR	361.16 EUR 361.16 EUR
Standard	...	TCP/IP
Supported resolutions	...	max. 12 Mpx - 4000 x 3000 px
Mounting standard	VESA 100 x 100, 75 x 75	...
Screen size range	13 " ... 27 "	...
Video outputs	...	<ul style="list-style-type: none"> • 1 pcs HDMI 4K • 1 pcs HDMI • 1 pcs VGA
Bearing capacity	8 kg	...
Color	Black	...
Tilt adjustment	-60 ° ... 60 °	...
Horizontal rotation	360 °	...
Audio support	...	<ul style="list-style-type: none"> • 32 Channels - Audio from cameras, • Bi-directional audio streaming support • Compliance with the AAC standard
Rotation in the plane of the screen	360 °	...
Audio inputs	...	1 pcs CINCH
Audio outputs	...	1 pcs CINCH
Main features	<ul style="list-style-type: none"> • Mount tube length 40 cm • Distance 17 cm in the bolt axis 	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264
Bitrate	...	320 Mbps
Supported hard drives	...	8 x 10 TB SATA + 1 x eSATA
Recording modes	...	Manual, Sensor, Motion detection, Schedule
External storage devices backup	...	Records backup at (.avi) format to USB (pendrive)
Searching and playback the records	...	Records searching: timeline or file list. Playback: forward, fast Playback max. 16 cameras in the same time @ 1080p

Network interface	...	2 x RJ-45 10/100/1000 Base-TX
Network functions	...	Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters
Network protocols	...	IPv6, TCP/IP, HTTP, HTTPS, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, P2P, PPPoE
ONVIF	...	✓
Default IP address	...	192.168.1.88
Default admin user / password	...	admin / 12345
Web browser access ports	...	80, 5000, 554
PC client access ports	...	80, 5000, 554
Mobile phones support	...	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision, Android: Free application iVMS320 • Android: Free application BitVision, iOS: Free application iVMS320
USB	...	<ul style="list-style-type: none"> • 2 pcs USB 2.0 • 1 pcs USB 3.0
Serial ports	...	RS-485
Alarm inputs / outputs	...	16 / 4
PTZ control	...	<ul style="list-style-type: none"> • IP Speed Dome Cameras • RS-485 control
Motion Detection	...	Split the screen into zones : 22 x 18 motion zones
Intelligent image analysis	...	✓
Main features	...	<ul style="list-style-type: none"> • Support for intelligent image analysis, available in cameras from the APTI-AI series • D-ZOOM - Digital Zoom
Mouse support	...	✓
IR remote controller in the set	...	—
Switch PoE	...	—
Power supply	...	100 ... 240 V AC, 50 / 60 Hz
Power consumption	...	≤ 20 W (without HDD)
Operation temp	...	-10 °C ... 50 °C
Weight	2.07 kg	7.41 kg
Dimensions	515 x 262 x 117 mm	440 x 430 x 100 mm

Supported languages	...	Polish, English, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Ukrainian, Italian
Manufacturer / Brand	RED EAGLE	APTI
Guarantee	2 years	2 years