




	ACCESS POINT RG-RAP2260(H) Wi-Fi 6 2.4 GHz 5 GHz 1148 Mbps + 4804 Mbps REYEE	AC POWER SUPPLY ADAPTER TR-40VA/NORATEL SATEL
		
	288.51 CHF 288.51 CHF	26.85 CHF 26.85 CHF
Adapter type	...	Transforming
Power voltage	...	230 ... 250 V AC
Output voltage	...	16 V, 18 V AC
Frequency range	2.4 GHz (2.400 ... 2.4835 GHz) 5 GHz (5.150 ... 5.850 GHz)	47 ... 63 Hz
Maximal load	...	2.22 A
EN norm	...	EN61558-2-6
Test voltage between PRI/SEC	...	AC 4kV RMS
Safety class	...	II
Isolation class	...	B (130°C)
"Index of Protection"	...	IP44
Output power	...	40 VA
Antenna type	4x4 MU-MIMO, 2.4 GHz - 3 dBi / 5.0 GHz - 4 dBi, Integrated - 8 x Omnidirectional antenna	...
Standards	IEEE 802.11 a/b/g/n/ac/ax	...
Application	...	<ul style="list-style-type: none"> • to alarm systems powering • to automatic systems • to low-voltage light installation powering
Output	...	2 pcs
Baud rates	1148 Mbps + 4804 Mbps	...
Wireless transmission range	40 m - 2.4 GHz 70 m - 5 GHz	...
Default IP address	10.44.77.254	...
Protections	WPA-PSK, WPA2-PSK, WPA/WPA2-PSK	...
LAN ports	2 x 10/100/2500 Mbps	...
Mobile phones support	Android: Free application Ruijie Reeye iOS (iPhone): Free application Ruijie Reeye	...

Transmitter power	≤ 35 dBm @ 2.4 GHz (max) ≤ 36 dBm @ 5.0 GHz (max)	...
Power supply PoE	PoE (802.3bt)	...
Power supply	48 V / 1 A (power adapter not included)	...
Power consumption	≤ 40 W	...
Main features	<ul style="list-style-type: none"> • Possibility to mount on the wall or ceiling • Support for Reye Mesh technology • Number of users : 512 (max) • OFDMA • WMM (Wi-Fi Multimedia) <p>Access Point is managed through the web and the cloud (Ruijie Reye application)</p> <ul style="list-style-type: none"> • Load balance • AP placement and RF maps • Easy and uniform management system for many devices • Intuitive installation and configuration of many advanced functions • Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source • Seamless Roaming - 802.11k/v roaming function switches clients automatically to the AP with the optimal signal with a seamless transition when moving. This allows sensitive applications like VoIP and video conferences to go uninterrupted 	...
Operation temp	0 °C ... 40 °C	...
Permissible relative humidity	5 % ... 95 %	...
Weight	1.4 kg	1.01 kg
Dimensions	231 x 231 x 56 mm	124 x 72 x 67 mm
Manufacturer / Brand	RUIJIE / REYEE	SATEL

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Guarantee	3 years	2 years
-----------	---------	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00