




	<a href="#">IP VANDALPROOF CAMERA DS-2CD1143G2-LIU(2.8MM) Smart Hybrid Light - 3.7 Mpx Hikvision</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1400TL-0280B - 3.7 Mpx 2.8 mm DAHUA</a>
		
	172.41 EUR 172.41 EUR	79.24 EUR 79.24 EUR
Standard	TCP/IP	HD-CVI, HD-TVI, AHD, CVBS
Sensor	1/3 " Progressive Scan CMOS	1/2.7 " CMOS
Matrix size	4 Mpx	3.7 Mpx
White light LED illuminator range	30 m	...
Memory card slot	—	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Resolution	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	<ul style="list-style-type: none"> <li>• AHD / HD-CVI / HD-TVI : 2560 x 1440 - 3.7 Mpx ,</li> <li>• HD-CVI : 1920 x 1080 - 1080p ,</li> <li>• CVBS 960 x 576 - 960H, PAL</li> </ul>
Range of IR illumination	30 m	30 m
IR illuminator power adjustment	...	Automatic
Lens	2.8 mm	2.8 mm
View angle	98 °	<ul style="list-style-type: none"> <li>• 97 ° (manufacturer data)</li> <li>• 94 ° (our tests result)</li> </ul>
Main stream frame rate	<ul style="list-style-type: none"> <li>• 20 fps @ 3.7 Mpx</li> <li>• 25 fps @ 1080p</li> </ul>	...
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	6	...
ONVIF	✓	...
Video output	...	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio transmission via network</li> <li>• Compliance with the AAC standard</li> <li>• Noise and echo reduction</li> </ul>	—
OSD menu	...	OSD menu available via DAHUA recorder

Main features	<ul style="list-style-type: none"> <li>• Smart Hybrid Light technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• Possibility to turn off the LED illuminator</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Image rotation and mirror</li> <li>• Sharpness - sharper image outlines</li> <li>• video tampering</li> <li>• Configurable Privacy Zones</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> </ul>	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> <li>• Privacy zones</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul>
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">Hik-Connect</a></li> <li>• iOS: Free application <a href="#">Hik-Connect</a></li> </ul>	...
Default IP address	192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	<ul style="list-style-type: none"> <li>• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 500 mA</li> </ul>	12 V DC / 330 mA
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 7.5 W @ PoE</li> <li>• ≤ 6 W @ 12 V DC</li> </ul>	≤ 4 W
Housing	Dome, Metal + Plastic	Dome, Aluminum + Plastic
Color	White	White
"Index of Protection"	IP67	IP67
Vandal-proof	IK08	—
Operation temp	-30 °C ... 60 °C	-40 °C ... 60 °C
Weight	0.48 kg	0.22 kg
Dimensions	Ø 121 x 98 mm	Ø 97 x 86 mm
Supported languages	English, Ukrainian	...
Manufacturer / Brand	Hikvision	DAHUA
SAP Code	311322068	...
Guarantee	3 years	3 years


 DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00