




	CONNECTION BOX PUH-RJ45	ACCESS CONTROL PANEL CPR32-NET-BRD ROGER	DUAL SMART LIGHT TOUCH SWITCH ATLO-TB2-TUYA Wi-Fi, Tuya Smart
			
	5.23 GBP 5.23 GBP	275.92 GBP 275.92 GBP	8.56 GBP 8.56 GBP
Number of intakes	2
Connectors	2 x RJ-45 socket
Application	Works with lighting - switching on/off
"Index of Protection"	IP67
Inputs	...	<ul style="list-style-type: none"> • 8 pcs - Mainboard inputs • max. 32 	...
Rated voltage	100 ... 240 V AC, 50 / 60 Hz
Cable diameter	Ø 4 ... Ø 7 mm
Maximum power	300 W (for each output)
Rated current	max. 10 A
Application	Hermetic connection of two RJ45 patchcords - It is compatible with Category 5e
Outputs	...	<ul style="list-style-type: none"> • 6 pcs - Transistor outputs • 2 pcs - Relay outputs NO/NC 	...
Number of buttons	2 (touch)
Communication	...	<ul style="list-style-type: none"> • 2 x RS-485 	...
Number of outputs	2
Connector type	screw terminals
Events memory	...	<ul style="list-style-type: none"> • Events saving to the micro SD card (not included) • Recording up to 240 000 events from the control panel 	...
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Mobile phones support	<ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Output load	...	<ul style="list-style-type: none"> • Transistor outputs : 1 A / 15 V DC • Relay outputs : 1.5 A / 30 V DC 	...

Main features	...	<ul style="list-style-type: none"> • Ability to block/unblock partition at a specified time, or as per access schedule, • Central management of the access control system, • Integration with the alarm system SATEL INTEGRA, • History of 250 000 events • Electrical protection of all inputs and outputs as well as communication buses • Full support via network 	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control, • LED indication • Backlit, touch control panel • The product does not fit standard mounting boxes with a diameter of 60 mm
Housing	Plastic + Acrylic glass (plexiglass)
Power supply	...	<ul style="list-style-type: none"> • 24 V DC • 12 V DC • 18 V AC 	...
Color	White
Battery backup support	...	✓	...
Operation temp	...	5 °C ... 40 °C	-20 °C ... 50 °C
Permissible relative humidity	...	10 % ... 95 % (non-condensing)	≤ 80 %
Dimensions	109 x 30 x 30 mm	175 x 81 x 50 mm	86 x 86 x 34 mm
Weight	0.04 kg	0.15 kg	0.134 kg
Manufacturer / Brand	...	ROGER	...
Guarantee	2 years	3 years	2 years