





	<a href="#">BROADBAND ANTENNA ASP-4</a>	<a href="#">ELECTRICAL INSTALLATION CONNECTION KZ-20</a>	<a href="#">MULTIPURPOSE WIRELESS DETECTOR AXD-200-DG (Multipurpose Detector DG) ABAX/ABAX2 SATEL</a>	<a href="#">CODE LOCK SZW-02 SATEL</a>
				
	11.15 EUR 11.15 EUR	0.27 EUR 0.27 EUR	51.92 EUR 51.92 EUR	26.44 EUR 26.44 EUR
Inner diameter	...	Ø 20 mm	...	...
Support	...	...	ABAX/ABAX2	...
Receiving channels	6 ... 60	...	...	...
Relay contacts load	...	...	...	max. 2 A
Alarm signaling	...	...	Signal to control panel	...
Pipe mounting method	...	Pressing	...	...
Gain	3.5 ... 10.5 dB	...	...	...
Frequency band	...	...	868 MHz ... 868.6 MHz	...
Polarization	Horizontal	...	...	...
Impedance	75 Ω	...	...	...
Main features	...	...	...	<ul style="list-style-type: none"> <li>• relay for electromagnetic lock/electric strike</li> <li>• Alarm output</li> <li>• Microswitch as tamper contact</li> <li>• LEDs indicating device operation state</li> <li>• Green backlight of the keys</li> </ul>
Power supply	...	...	...	9 V ... 16 V DC
Current consumption	...	...	...	max. 60 mA
Radio communication range (at open area)	...	...	<ul style="list-style-type: none"> <li>• ~ 500 m @ ABAX,</li> <li>• ~ 2000 m @ ABAX2</li> </ul>	...
Battery	...	...	CR123A 3 V - 3.0 V (included)	...
Backup time	...	...	~ 2 years	...
Protection class (Grade)	...	...	2	...

Main features	<ul style="list-style-type: none"> <li>• Number of elements : 10</li> <li>• Matching transformer included</li> </ul>	The corrugation of the connection enables its bend	<ul style="list-style-type: none"> <li>• Operation modes : <ul style="list-style-type: none"> <li>- Magnetic detector</li> <li>- Dual channel magnetic detector</li> <li>- Magnetic detector with roller shutter input</li> <li>- Shock and magnetic detector - Detection of shocks and vibrations associated with attempts to force a door or window</li> <li>- Reorientation detector - Detecting a change in position of an object</li> <li>- Temperature Sensor - Temperature measurement in the range: -10°C ... +55°C, Two programmable temperature thresholds (upper and lower)</li> <li>- Water flood detector - The required FPX-1 probe is available separately</li> <li>- 2 x NC wired zone expander</li> <li>- Wired zone expander: NC and roller shutter</li> </ul> </li> <li>• Tamper detection - opening the enclosure, removing from mounting surface</li> <li>• Remote configuration</li> <li>• Remote update of module software</li> <li>• The LED to indicate violations in test mode, easy start-up and later maintenance of the system</li> </ul>	...
Operation temp	...	...	-10 °C ... 55 °C	-10 °C ... 55 °C
Color	...	White	Dark graphite	...
Weight	...	...	0.023 kg	0.16 kg
Dimensions	450 x 600 x 250 mm	Ø 22 x 140 mm	20 x 102 x 23 mm	150 x 85 x 26 mm
Manufacturer / Brand	...	...	SATEL	SATEL
Guarantee	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00