



	IP CAMERA TC-C34WP SPEC:W/E/Y/2.8MM/V4.0 Color Maker 2.8 mm TIANDY	RUBBER MAT MB-GUM/50
		
	189.54 EUR 189.54 EUR	6.20 EUR 6.20 EUR
Standard	IP	...
Application	...	<ul style="list-style-type: none"> • Area covering, • Soundproofing
Material	...	SBR granulate + polyurethane binder
Main features	...	<ul style="list-style-type: none"> • Rough structure • Granule fraction : 0.5 ... 4 mm • Insulation • High fatigue strength of the material • Weatherproof • Very easy and quick assembly
Resolution	2592 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Sensor	1/2.8 " Progressive Scan CMOS	...
Lens	2.8 mm	...
View angle	<ul style="list-style-type: none"> • 100 ° (manufacturer data) • 90 ° (our tests result) 	...
White light LED illuminator range	15 m	...
Memory card slot	Micro SD card support up to 512GB	...
Image compression method	S+265 / H.265 / H.264	...
Alarm inputs / outputs	—	...
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network 	...
Main stream frame rate	25 fps @ 4 Mpx	...
Interface	10/100 Base-TX (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	2	...
ONVIF	✓	...

Mobile phones support	Port no.: 3000 or access by a cloud (P2P) • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus	...
Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express	...
Default IP address	DHCP or 192.168.1.2	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 443, 3000, 3001, 3002, 23002	...
Mobile client access ports	3000, 3001	...
PC client access ports	3000, 3001	...
Port ONVIF	80	...
Intelligent image analysis	<ul style="list-style-type: none"> • crossing the line (tripwire) • intrusion • video tampering 	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • AGC - Automatic Gain Control • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • BLC/HLC - Back Light / High Light Compensation • Color maker - colorful night mode • Motion Detection 	...

Power supply	• PoE (802.3af), • 12 V DC / 590 mA	...
Power consumption	≤ 7 W	...
Housing	Compact - Metal + Plastic	...
Color	White	Black
"Index of Protection"	IP67	...
Mechanical protection class	—	...
Operation temp	-40 °C ... 65 °C	...
Weight	0.3 kg	2.4 kg
Dimensions	160 x 73 x 73 mm	500 x 500 x 10 mm
Supported languages	Polish, English, Albanian, Arabic, Spanish, Korean, French, Dutch, Hebrew, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian	...
Manufacturer / Brand	TIANDY	...
Guarantee	3 years	...