







	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE56D0T-IRMMEIG (6mm) - 1080p Hikvision	POLE MOUNT DS-1275ZL-SUS Hikvision	CABLE TIE HOLDER PS-4-19X19/R*P100	SMART LED LIGHTING CONTROLLER W/LIGHTBOX-S-PRO/BLEBOX Wi-Fi, 12... 24 V DC	IP VANDAL-PROOF CAMERA DS-2CD1147G2H-LIU/2.8MM/PL Smart Hybrid Light - 3.7 Mpx Hikvision	ELECTRIC CABLE YKY-5X6-0
						
	528.97 NOK 528.97 NOK	640.92 NOK 640.92 NOK	69.97 NOK 69.97 NOK	384.58 NOK 384.58 NOK	2328.58 NOK 2328.58 NOK	63.36 NOK 63.36 NOK
Suitable for cameras	...	Hikvision
Application	Works with LED lighting - single-color (MONO) 12-24V LED strips
In section	100 m . Price for 1m when buying a whole roll
Pole diameters range	...	Ø 67 ... Ø 127 mm
Standard	AHD / HD-CVI / HD-TVI / PAL	IP	...
In package	100 pcs The price for package
Material	...	Stainless steel
Holes dimensions	3.5 x 1.5 mm
Matrix size	2.1 Mpx
Montage hole diameter	Ø 5 mm
Maximal total load	120 W
Inner conductor	5 x 6.0 mm ² - Cu wire
Total maximal current	5 A
Rated voltage	12 ... 24 V DC	...	0.6 / 1 kV
Resolution	1920 x 1080 - 1080p	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...
Number of inputs	1
Assembly	• The bottom layer is equipped with a Scotch tape, • Mounting with screws
Number of outputs	1
Outer coating	Ø 17.2 mm - PVC
Sensor	Progressive Scan CMOS	1/3 " Progressive Scan CMOS	...
IR illuminator power adjustment	Automatic
Connector type	screw terminals
Coating color	Black
Lens	3.6 mm	2.8 mm	...
Range of IR illumination	20 m	30 m	...
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g
White light LED illuminator range	30 m	...
Memory card slot	—	...
View angle	• 82 ° (manufacturer data) • 78 ° (our tests result)	96 °	...
IR illuminator support	ICR - Movable InfraRed filter
S/N ratio	> 62 dB
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Video output	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI, BNC socket
Audio	• Microphone built-in • Audio transmission via network • Compliance with the AAC standard • Noise and echo reduction	...
Main stream frame rate	• 20 fps @ 4 Mpx • 25 fps @ 1080p	...
OSD menu	—
Network interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	6	...
Main features	• Local control by physical button, • schedule, • timer, • remote access, • voice control, • Lighting on/off and brightness control, • Absence mode - enables random turn on and off the lighting simulating the presence of household members, • Omnidirectional antenna Wi-Fi 5 dB, • SMA-RP socket • µWiFi technology support
ONVIF	✓	...
Vandal-proof	—
Operation temp	20 °C ... 50 °C

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Day/night mode • BLC - Back Light Compensation • Auto White Balance 	<ul style="list-style-type: none"> • Smart Hybrid Light technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • Sharpness - sharper image outlines • video tampering • Configurable Privacy Zones • Smart motion detection (with recognizing people and vehicles) 	...
Mobile phones support	<ul style="list-style-type: none"> • The wBox free application on Android • The wBox free application on iOS 	<ul style="list-style-type: none"> Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect 	...
Default IP address	192.168.1.64	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ 	...
Power supply	12 V DC / 330 mA	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA 	...
Power consumption	≤ 4 W	<ul style="list-style-type: none"> • ≤ 7.5 W @ PoE • ≤ 6 W @ 12 V DC 	...
Housing	Dome, Plastic	<ul style="list-style-type: none"> • Non-halogen plastic, Self-extinguishing • Waterproof, Weatherproof 	Dome, Metal + Plastic	...
Color	White	White	Black	Black	White	...
"Index of Protection"	IP44	IP54	IP67	...
IK rating	IK08	...
Operation temp	-20 °C... 45 °C	-30 °C... 60 °C	...
Weight	0.15 kg	1.5 kg	...	0.094 kg	0.48 kg	...
Dimensions	Ø 98 x 66 mm	127 x 250 x 46 mm	19 x 19 x 5.5 mm	<ul style="list-style-type: none"> • 92 x 52 x 28 mm - without antenna • 230 x 85 x 28 mm - with antenna, vertical • 197 mm - Antenna 	Ø 121 x 98 mm	...
Supported languages	Polish	...
Manufacturer / Brand	Hikvision	Hikvision	...	BleBox	Hikvision	...
SAP Code	300609197	302701533	311327306	...
Guarantee	3 years	3 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00