



	END CLAMP PV-KK/35-50/B FOR SOLAR PANELS 35 mm	SURFACE-MOUNTED TELECOMMUNICATION BOX TESM-4/N	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-TA15FR4 - 8.3 Mpx, 4K UHD 3.6 mm BCS BASIC
			
	0.62 EUR 0.62 EUR	49.18 EUR 49.18 EUR	39.34 EUR 39.34 EUR
Height	35 mm
Application	...	<ul style="list-style-type: none"> • R-TV SAT • WLAN 	...
Hole diameter	9 mm
Material	Aluminum	Steel	...
mounting screw	—
Standard	AHD, HD-CVI, HD-TVI, PAL
Sensor	1/2.5 " Progressive Scan CMOS
Matrix size	5 Mpx
Main features	...	<ul style="list-style-type: none"> • Prefabricated mounting plate with dimensions: 280 x 200 mm • 2 keys included • Very easy and quick assembly • Aesthetic and solid construction • The housing passes the WiFi signals, • Place for connectors : 8x KEYSTONE, 6x "F", 1x SC duplex, 1x Electric outlet 	...
Internal dimensions	...	280 x 250 x 65 mm	...
External dimensions	...	340 x 420 x 90 mm	...
Resolution	3840 x 2160 - 8.3 Mpx, 4K UHD , 2704 x 1950 - 5.3 Mpx @ AHD / HD-TVI , 2560 x 1440 - 4 Mpx , 1920 x 1080 - 1080p 960 x 576 - 960H, PAL
Lens	3.6 mm, F1.2
Dimensions of the cable entry holes	...	<ul style="list-style-type: none"> • 2x Ø 60 mm - from the bottom • 3x Ø 50 mm - in the back 	...
View angle	<ul style="list-style-type: none"> • 100 ° (manufacturer data) • 94 ° (our tests result)
Range of IR illumination	40 m

IR illuminator power adjustment	Automatic
Video output	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω, selectable by switch
OSD menu	✓
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Sharpness - sharper image outlines • AGC - Automatic Gain Control • White Balance - ATW/Manual • Day/night mode • ICR - Movable InfraRed filter • Mirror - Mirror image
Power supply	12 V DC / 420 mA
Power consumption	≤ 5 W
Housing	Compact, Metal
Color	Black	White	White
"Index of Protection"	IP66
Operation temp	-20 °C ... 60 °C
Weight	0.22 kg	3.77 kg	0.44 kg
Dimensions	50 x 38 x 28 mm	...	Ø 69 x 184 mm
Manufacturer / Brand	BCS BASIC
Guarantee	2 years	2 years	3 years