



	UPS AT-UPS3000RT/3-RACK 3000 VA EAST	SPEAKER CABLE HI- FI/2X0.5
		
	732.91 GBP 732.91 GBP	0.26 GBP 0.26 GBP
Power adapter type	Online	...
Nominal power	2700 W	...
Apparent Power	3000 VA	...
In section	...	100 m . Price for 1m when buying a whole roll
Input voltage	230 V AC \pm 25 %	...
Input frequency	50 / 60 Hz (auto detection)	...
Inner conductor	...	2 x \varnothing 0.5 mm Cu-OFC Stranded wire
Outer coating	...	PVC
Output voltage	230 V AC \pm 5 % (Pure Sine Wave)	...
Coating color	...	Colorless
Output frequency	50 / 60 Hz	...
Voltage adjustment	\pm 1 %	...
Frequency adjustment	—	...
Transfer time	4 ms	...
Charging time (recover to 90% capacity)	8 hours	...
Battery	8 x 12V/9Ah	...
Estimated battery operation time	<ul style="list-style-type: none"> • 120 minutes @ 200 W, • 60 minutes @ 400 W, • 40 minutes @ 600 W, • 25 minutes @ 800 W, • 20 minutes @ 1000 W, • 12.5 minutes @ 1200 W, • 9 minutes @ 1600 W, • 7.5 minutes @ 1800 W, • 6.5 minutes @ 2000 W, • 5 minutes @ 2400 W, • 4 minutes @ 2700 W 	...
Number of outputs	6 pcs IEC-320 C13	...
Management software	UPSmart (Windows 95/98/2000/XP/Vista/7/8/10, Linux)	...
Protections	<ul style="list-style-type: none"> • Fuse • Overvoltage • Overload protection • EPO (Emergency power off) switch • Ethernet filter 	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Operation state indication	<ul style="list-style-type: none"> • LCD display: operation mode, battery charging level, in/out voltage level, overload indicator, • Sound signaling 	...
Main features	<ul style="list-style-type: none"> • Auto restart while AC is recovering • Automatic Voltage Regulator (AVR) • "Cold Start" function • Compatible with power generators • Remote management - UPSmart application included • Built-in EMI, RFI filter • Excellent microprocessor control guarantees high reliability • UPS auto diagnostic system • Battery charge and maintenance control • USB/RS-232 communication port 	...
Application	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment 	...
Housing type	Rack/Tower 2-in-1 Design	...
Operation temp. / Relative humidity	0 °C ... 40 °C / 0 ~ 90 % (non-condensing)	...
Weight	38.4 kg	...
Dimensions	2 pcs : 440 x 85 x 468 mm RACK 19", 2U	...
Manufacturer / Brand	EAST	...
Guarantee	2 years	2 years