

	TV OR MONITOR MOUNT BBATECK-4P77-441	SWITCHING ADAPTER 12V/21A/PA18	IP CAMERA (IPC-IP093441E-ZAS-27135 - 4 Mpx 2.7" - 13.5 mm - MOTOZOOM DAHUA	ANGULAR COUPLER LMA LX50R	HUB USB 3.0 PAPRAL UL015-BK-E2	BATTERY 12V/18Ah SBL-SSB	MONITORS DESK MOUNT MC-691-MAC/LEAN	CONNECTOR FOR LED STRIPS AD-TL-6495/ZT 8 mm UBRN1	CONNECTOR FOR LED STRIPS AD- TL-6495/ZT-10mm UBR2	POWER DISTRIBUTION UNIT MCE-10-110 MUTLETS 1.5 m MAC/LEAN
										
Adapter type	11.99 EUR 11.99 EUR	Switching	341.56 EUR 341.56 EUR	1.82 EUR 1.82 EUR	7.10 EUR 7.10 EUR	38.02 EUR 38.02 EUR	61.05 EUR 61.05 EUR	0.90 EUR 0.90 EUR	0.98 EUR 0.98 EUR	13.74 EUR 13.74 EUR
Battery capacity						18 Ah				
Standard			DC/PIP							
Length				100 mm						
Width				100 mm						
Application								Works with LED lighting	Works with LED lighting	
Output voltage		12 V DC								
Sensor			1/3" Progressive Scan CMOS							
Rated voltage						12 V				230 V AC / 50 Hz
Depth				27.5 mm						
Strip width							8 mm	10 mm		
Battery charging current			4 Mpx							
Main size						max. 5.4 A				
Total maximal current										16 A
Maximal total load										3680 W
Material				PVC						
Output voltage adjustment	11 ... 13 V									
Connectors						* 1 x plug - USB-A * 4 x socket - USB-A				
Battery type						Maintenance-free AGM (Absorbent Glass Mat) battery				
LED indication		<input checked="" type="checkbox"/>								
Length of the cable					15 cm					
Connector						M5 screw				
Max. output current (total)		21 A								
USB standard					3.0					
Maximal power voltage							48 V	48 V		
Max. output current for single output		1.1 A								
Battery lifetime						10 ... 12 years				
Number of outlets										2 x 5 grounded outlets (6A/250V, E type (CEE 7:5))
Input voltage		230 V AC								
Power		252 W								
Horizontal rotation							180°			
Fuse										16 A / 250 V
Number of outputs		18								
Mounting standard	VESA 100, 150, 200, 200x100, 300, 300x200, 400x200, 400x300, 400						VESA 75, VESA 100			
Rotation in the plane of the screen							360°			
Connector type			Cable terminals							
Mount tube diameter							Ø 35 mm			
Housing type		Metal, wall-mounted								
Screen size range	32" ... 70"						13" ... 27"			
Switch										2 pcs - illuminated, each for a section of 5 outlets
Key closed		<input checked="" type="checkbox"/>								
Bearing capacity	75 kg						8 kg			3 x 1.5 mm
Wire gauge										
Distance from mounting surface	47 mm									
Length of the cable										1.5 m
Resolution			2688 x 1520 - 4 Mpx. 2304 x 1296 - 3 Mpx. 1920 x 1080 - 1080p. 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p							
Tilt adjustment	10° ... 4°						45° ... 45°			
Lens			2.7" ... 13.5 mm - Motorzoom							
View angle			* 104° ... 27° (manufacturer data) * 101° ... 27° (our tests result)							
Range of IR illumination			40 m							
RS-485 interface										
Memory card slot			Micro SD memory cards up to 256GB support (possible local recording)							
Image compression method			H.265+ / H.265 / H.264+ / H.264 / MJPEG							
Alarm inputs / outputs										
Audio										
Bitrate			3 ... 8192 kbps							
Network interface			10/100 Base-T (RJ-45)							
Network protocols			HTTP, HTTPS, IP+IPv6, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, POP3, IEEE 802.1x, Bonjour							
WEB Server			Built-in, Web Viewer							
Max. number of on-line users			20							
ONVIF			18.06							
Mobile phones support			Port no. 37777 or access by a cloud (P2P) * Android: Free application DMSS * iOS (iPhone): Free application DMSS							
Default IP address			192.168.1.108							
Default admin user / password			admin / The administrator password should be set at the first start							
Web browser access ports			80, 37777							
PC client access ports			37777							
Mobile client access ports			37777							
Port ONVIF			80							
RTSP URL			rtsp://admin.haskb@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 Main stream rtsp://admin.haskb@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 Sub stream							
Main stream frame rate			25 fps @ 4 Mpx							
Main features			* Motorzoom lens - Controlling from browser, NVR or software * WDR - 120 dB - Wide Dynamic Range * 3D-DNR - Digital Noise Reduction * ROI - improve the quality of selected parts of image * ICR - Movable InfraRed filter * BLC - configurable Back Light Compensation * HLC - High Light Compensation (opt) * IVS analysis : crossing the line (tripwire), intrusion, Smart motion detection (with recognizing people and vehicles) * D-ZOOM - Digital Zoom * Day/Night mode (color/b&w/auto) * Configurable Privacy Zones							
Power supply			* PoE (802.3af), * 12 V DC / 690 mA							
Power consumption			< 8.3 W							
Housing			Dome - Metal							Plastic
Color	Black		White	Black			Black	White	White	Black
Vandal-proof										
"Index of Protection"			IP67							
Operation temp			-30 °C ... 60 °C							
Weight	2 kg	1.88 kg	0.7 kg	0.03 kg	0.035 kg	4.8 kg	6 kg	0.002 kg	0.002 kg	0.968 kg
Dimensions	570 x 430 x 47 mm	215 x 317 x 65 mm	Ø 122 x 105 mm		88 x 24 x 13 mm	181 x 77 x 167 mm	1330 x 550 x 83 mm	25 x 17 mm	20 x 20 mm	78 x 70 x 45 mm

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Supported languages	-	-	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian	-	-	-	-	-	-	-
Manufacturer / Brand			DAHUA		ORICO		MACLEAN	ORNO	ORNO	MACLEAN
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00