



	<a href="#">BATTERY 12V/80AH-MWL</a>	<a href="#">AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR BCS-L- XVR1601-4KE-IV 16 CHANNELS BCS Line</a>
		
	172.04 EUR 172.04 EUR	674.14 EUR 674.14 EUR
Battery capacity	80 Ah	...
Rated voltage	12 V	...
Battery charging current	max. 24 A	...
Battery type	Maintenance-free AGM (Absorbent Glass Mat) battery	...
Connector	M6 screw	...
Standard	...	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Video inputs	...	16 pcs BNC
Battery lifetime	10 ... 12 years	...
Video outputs	...	1 pcs HDMI 4K 1 pcs VGA
Audio inputs	...	1 pcs CINCH 16 Channels - Audio support via coaxial cable, HD-CVI only
Audio outputs	...	1 pcs CINCH
Image compression method	...	AI Coding / H.265+ / H.265 / H.264+ / H.264
Image records resolutions	...	<ul style="list-style-type: none"> <li>• AHD / HD-CVI / HD-TVI : 8 Mpx - 3840 x 2160 , 4K-N - 1920 x 2160 , 6 Mpx - 2880 x 1920 - HD-CVI only , 5 Mpx - 2592 x 1944 , 4 Mpx - 2560 x 1440 , 4M-N - 1280 x 1440 , 3 Mpx - 2048 x 1536 - AHD / HD-TVI only , 1080p - 1920 x 1080 , 720p - 1280 x 720</li> <li>• CVBS : 960H - 960 x 576</li> <li>• IP : max. 8 Mpx - 3840 x 2160</li> </ul>

Recording speed adjustment	...	8 Mpx IP @ 1 ... 25 fps 8 Mpx @ 1 ... 7 fps 4K-N @ 1 ... 15 fps 6 Mpx @ 1 ... 10 fps 5 Mpx @ 1 ... 12 fps 4 Mpx @ 1 ... 15 fps 4M-N @ 1 ... 25 fps 3 Mpx @ 1 ... 15 fps 1080p @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel
Operation modes	...	16 x AHD / HD-CVI / HD-TVI / CVBS / IP + 16 x IP
Recording modes	...	Manual, Motion Detection, Schedule
Supported hard drives	...	1 x 16 TB SATA
External storage devices backup	...	Save single frames and whole records from DVR drive to the USB drive
Searching and playback the records	...	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function 1/4/9/16 channel synchronous playback
Network functions	...	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users
USB	...	1 x USB 2.0 1 x USB 3.0
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) • Android: Free application <a href="#">BCS Manager</a> • iOS (iPhone): Free application <a href="#">BCS Manager</a>
Alarm inputs / outputs	...	—
PTZ control	...	IP Speed Dome Cameras Control compatible with coax PTZ HD-CVI RS-485 - PELCO-D/P

Motion Detection	...	Split the screen into zones : 22 x 18 motion zones
Main features	...	<ul style="list-style-type: none"> <li>• Privacy zones - max. 4</li> <li>• SMD PLUS - searching for an object classified as: human, motor vehicle,</li> <li>• POS - support the machines installed in the points of sales and displaying the date from them as overlaid text on selected channel window,</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, face detection</li> </ul>
Mouse support	...	✓
IR remote controller in the set	...	✓
Power supply	...	12 V DC / 3 A (power adapter included)
Color	...	Black
Weight	23.4 kg	1.41 kg
Dimensions	255 x 166 x 205 mm	325 x 256 x 55 mm, RACK 19", 1U
Supported languages	...	Polish, English
Manufacturer / Brand	...	BCS Line
Guarantee	2 years	3 years