



	ACCESS CONTROLLER ASC2204B-S DAHUA	ACCESS CONTROLLER MODULE MC16-PAC-EX-3 ROGER
		
	283.89 EUR 283.89 EUR	687.50 EUR 687.50 EUR
Number of served transitions	4 (one-way)	3
Support	DAHUA	...
Inputs	...	18
Number of supported readers	4 pcs	...
Outputs	...	12
Number of users	...	max. 12000 - Number of identifiers
Output lines	5 pcs - Relay	...
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.
Number of permissions per ID	...	100
Buffer memory	...	8 000 000 events buffer
MCT readers support	...	16 pcs
Readers connections	...	4 pcs - Wiegand / PRT
Number of login points	...	6
Number of access terminals	...	12
Number of access zones	...	6
Number of alarm zones	...	6
Number of automation nodes	...	6
Battery backup support	—	12 V / 7 Ah
Default IP address	192.168.0.2	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Communication	<ul style="list-style-type: none"> • RS-485, • Ethernet, • Wiegand 	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RS-485 interface • RACS 5 v2 (Roger)

Main features	<ul style="list-style-type: none"> • 100000 indexed users • History of 150000 events • Remote programming from PC • Function of protection against multiple use of the same card for access (anti-passback) • Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value • Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress 	<ul style="list-style-type: none"> • Integrated support in VISO EX software • Functions in the VISO EX system: - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems)
Power supply	12 V DC / 1.4 A	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Operation temp	-30 °C ... 60 °C	5 °C ... 40 °C
Permissible relative humidity	max. 95 % (non-condensing)	10 % ... 95 % (non-condensing)
Weight	0.354 kg	0.14 kg
Dimensions	207 x 116 x 52 mm	175 x 72 x 30 mm
Manufacturer / Brand	DAHUA	ROGER
Guarantee	3 years	3 years