





| | WEATHER STATION UT-A13T UNI-T | CABLES TESTER HDMI UT-681-HDMI UNI-T | UNIVERSAL METER ST-6986 DVB-T/T2 DVB-S/S2 DVB-C SIGNAL | MOUNT RACK FRAME U19-3U/340 |
|----------------------------------|---|---|--|---|
| |  |  |  |  |
| | 13.67 EUR 13.67 EUR | 22.28 EUR 22.28 EUR | 359.62 EUR 359.62 EUR | 18.69 EUR 18.69 EUR |
| Tested cables | ... | HDMI, mini HDMI | ... | ... |
| Measurement | Temperature / relative humidity | ... | ... | ... |
| Material | ... | ... | ... | Steel - powder painted |
| Internal depth | ... | ... | ... | 285 mm |
| Measurement range | -10 °C ... 50 °C ± 1 °C | ... | ... | ... |
| Measurement of humidity | 20 % ... 95 % ± 5 % | ... | ... | ... |
| Output and input | ... | ... | <ul style="list-style-type: none"> Inputs : IEC - Ant socket, "F" - LNB socket, HDMI, AV - mini Jack input, SC / FC fiber optic input Outputs : HDMI, AV - mini Jack output, Power output, 12 V DC | ... |
| Color | White | ... | ... | Black (RAL 9005) |
| Operation temp | -10 °C ... 50 °C | ... | ... | ... |
| Frequency range | ... | ... | <ul style="list-style-type: none"> • 48 MHz ... 862 MHz @ DVB-T / DVB-T2 / DVB-C, • 950 MHz ... 2150 MHz @ DVB-S / DVB-S2 | ... |
| Permissible relative humidity | max. 90 % (non-condensing) | ... | ... | ... |
| Signal level | ... | ... | <ul style="list-style-type: none"> • -20 ... +80 dBm @ DVB-S / DVB-S2, • -20 ... +80 dBm @ DVB-T / DVB-T2 / DVB-C, • -40 ... +23 dBm - Optical power meter | ... |
| LNB power supply | ... | ... | 13 / 18 V, max. 400 mA | ... |
| Switching between bandwidths | ... | ... | 0 / 22 kHz | ... |
| Antenna powering | ... | ... | 5 / 12 / 24 V @ 100 mA | ... |
| DiSEqC | ... | ... | 1.0, 1.1, 1.2, 0/22 kHz Tone, Unicable (dSCR), Wideband systems support | ... |
| Modulation | ... | ... | QPSK / 8PSK / 16APSK @ DVB-S / DVB-S2 QPSK / 16-QAM / 64-QAM / 256-QAM @ DVB-T / DVB-T2 / DVB-C | ... |
| Video signal test | ... | ... | — | ... |
| Programming and firmware upgrade | ... | ... | via USB port | ... |
| Battery power supply | ... | ... | Li-Ion battery 7.4 V / 5000 mAh | ... |

| | | | | |
|----------------------|---|---|--|--------------------------------------|
| Power supply | 1 x battery LR3 (AAA) (included) | 9V, type 6F22 battery (included) | 12 V / 1.5 A (power adapter included) | ... |
| Power consumption | ... | ... | ≤ 10 W | ... |
| Main features | <ul style="list-style-type: none"> • LCD display • Digital sensor • Alarm function • Calendar function • Selectable measurement unit: °C / °F • Wall mounting • Integrated stand | <ul style="list-style-type: none"> • Test for the presence of a short circuit, open circuit • Single / full scan mode • Automatic shutdown after 10 minutes of inactivity • Low battery level alarm | <ul style="list-style-type: none"> • 7 " LCD display - 1280 x 720 px • Measurement of DVB-T/T2/C, DVB-S/S2 @ MPEG2/MPEG4 signals • Built-in DVB-S/S2, DVB-T/T2/C receiver allowing constant preview of the set channel • Built-in MPEG-2 / H.264 / H.265 video decoder • Calculation of azimuth and elevation angle • Constellation diagram • Analysis of the spectrum for the whole frequency band • Signal measurement expressed in dBμV, C/N, BER, MER • Measurement of signal strength and quality • Percent indication of signal quality • Built-in optical power meter - Optical wavelength : 850,1300, 1310, 1330, 1490, 1550, 1625 nm • The USB connector for supporting multimedia files wma, mp3, mp4, avi, jpg, jpeg, bmp, img • DisEqC automatic identification • High measurement accuracy • The set includes a practical case | ... |
| Weight | 0.106 kg | 0.132 kg | 1.17 kg | 1.76 kg |
| Dimensions | Ø 130 x 78 mm x 22 mm | 103 x 96 x 29 mm | 259 x 181 x 59 mm | 500 x 151 x 331 mm - RACK 19 " x 3 U |
| Supported languages | ... | ... | Polish, English, Czech, Danish, French, Greek, Spanish, Dutch, German, Slovenian, Portuguese, Russian, Turkish, Hungarian, Italian | ... |
| Manufacturer / Brand | UNI-T | UNI-T | SIGNAL | ... |
| Guarantee | 2 years | 2 years | 2 years | 2 years |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00