


	<a href="#">GROUNDING RESISTANCE METER UT-522 UNI-T</a>	<a href="#">TOOL BOX KHV40P</a>	<a href="#">POWER SUPPLY ADAPTER 12V/0.5A/TRF</a>	<a href="#">FLUX AGT-109 RF800 AG TERMOPASTY</a>
				
	191.34 CHF 191.34 CHF	7.87 CHF 7.87 CHF	6.16 CHF 6.16 CHF	3.75 CHF 3.75 CHF
Package	...	...	...	Plastic bottle
Model identifier	...	...	12V/0.5A/TRF	...
Flux marking in accordance with ISO 29454-1	...	...	...	1.1.3.A
Material	...	Plastic - mixture of increased strength polymers	...	...
Type of flux	...	...	...	rosin based
Input voltage	...	...	200 - 240 V AC	...
Kind of flux	...	...	...	halide-free, lead-free
AC input frequency	...	...	50 Hz	...
Form of flux	...	...	...	Liquid
Output voltage	...	...	12.0 V DC	...
Color	...	Black	...	Amber
Output current	...	...	0.5 A	...
Flash point	...	...	...	12 °C
Output power	...	...	6.0 W	...
Boiling temperature	...	...	...	82 °C
Average efficiency during work	...	...	78.9 %	...
Lower limit of explosion	...	...	...	2 %
Efficiency at low load (10%)	...	...	20.4 %	...
Upper limit of explosion	...	...	...	12 %
No-load power consumption	...	...	< 0.10 W	...
Adapter type	...	...	Transforming	...
Output voltage adjustment	...	...	—	...
Relative density	...	...	...	0.794 ( 1 = air )
Number of outputs	...	...	1 pcs	...
Flux solubility	...	...	...	easily soluble in cold and hot water
Package capacity	...	...	...	100 ml
Power connectors type	...	...	<ul style="list-style-type: none"> <li>• 230 V Plug</li> <li>• 12 V - 2.1/5.5 mm Straight plug</li> </ul>	...
Housing type	...	...	Desktop	...
External dimensions	...	384 x 335 x 144 mm	...	...

Resistance measurement	40 $\Omega \pm (2\% + 20)$ @ 0.01 $\Omega$ , 400 $\Omega \pm (2\% + 3)$ @ 0.1 $\Omega$ , 4000 $\Omega \pm (2\% + 3)$ @ 1 $\Omega$ • Auxiliary resistance : 500 $\Omega \pm 5\%$ • Measuring voltage : $\leq 10$ V AC @ ~820 Hz	...	...	...
Internal dimensions	...	365 x 245 x 110 mm	...	...
Ground voltage measurement	400 V $\pm (1.0\% + 6)$ @ 1 V	...	...	...
Automatic change of measuring ranges	—	...	...	...
RS-232	—	...	...	...
USB	—	...	...	...
Main features	<ul style="list-style-type: none"> <li>• Hold - stopping the meter reading,</li> <li>• The measurement can be performed in full or simplified configuration,</li> <li>• Warning of poor connection of leads during measurement,</li> <li>• Large, readable LCD display with backlight,</li> <li>• Low battery level alarm,</li> <li>• Aesthetic and solid construction,</li> <li>• The set includes a practical case</li> </ul>	<ul style="list-style-type: none"> <li>• High-strength body,</li> <li>• Ergonomic handle,</li> <li>• Protective foam inside to protect tools,</li> <li>• Capacity : 10 kg,</li> <li>• 2 fasteners on the front to prevent accidental opening</li> </ul>	...	...
Operation temp	5 °C ... 40 °C	...	...	...
Permissible relative humidity	$\leq 80\%$ (non-condensing)	...	...	...
Power supply	6 x 1.5V, type AA/LR6/FR6 battery - included	...	...	...
Weight	0.42 kg	0.95 kg	0.480 kg	...
Dimensions	160 x 100 x 70 mm	...	85 x 58 x 50 mm	...
Manufacturer / Brand	UNI-T	...	...	AG TERMOPASTY
Guarantee	2 years	2 years	2 years	2 years