







	EXTENDER HDMI+USB-EX-70	ALKALINE BATTERY BAT-LR43*P2 ENERGIZER	RFID PROXIMITY CARD ATLO-D194	SWITCHING ADAPTER 18V/1A/F-MRP FOR SIGNAL MRP MULTISWITCHES F PLUG	OVERVOLTAGE LIMITER LE-50670 2P+Z 2 x RJ45 3500 W LEGRAND	ISOPROPYL ALCOHOL KONTAKT-IPA-PLUS/100 BOTTLE 100 ml AG TERMOPASTY
						
	101.64 EUR 101.64 EUR	1.02 EUR 1.02 EUR	0.65 EUR 0.65 EUR	6.70 EUR 6.70 EUR	30.06 EUR 30.06 EUR	1.48 EUR 1.48 EUR
Adapter type	Switching
Supported HDMI resolutions	max. 1080p @ 60 Hz
Package	Bottle 100 ml
Standard	• 13.56 MHz S50, • Unique EM 125kHz
Maximal total load	3500 W	...
Application	Ideal for removing dirt from optical components
Power voltage	100 ... 240 V AC
Compatibility	ISO/IEC 14443A
In package	...	2 pcs The price for package
Total maximal current	16 A	...
Frequency range	50/60 Hz
Possibility of programming the serial number (ID)	—
Rated voltage	...	1.5 V	230 V / 50 Hz	...
Output voltage	18 V DC
Ability to write to internal memory	—
Nominal voltage of surge suppressor	250 V / 50 Hz	...
Maximal load	1 A
Serial Number overprint	—
Type (size)	...	LR43 / 186
Protection level of surge suppressor	1 kV	...
Application	SIGNAL MRP Multiswitches
Combined voltage pulse U _{oc}	4 kV	...
Output	F plug
Maximal transmission range	• 70 m - UTP cat. 6, 6A, 7 @ 1080p • 60 m - UTP cat. 5e @ 1080p (our tests result)
Number of outlets	2 pcs RJ45	...
Socket type	CEE 7/17	...
Plug type	CEE 7/7	...
Grounding	✓	...
Housing	Plastic	...
Main features	• Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse • Transition of the HDMI signal in the transmitter • EDID support • Audio transmission via network (Stereo)
Color	Gray / White	...
"Index of Protection"	IP20	...
IK rating	IK04	...
Main features	• Very good image quality with no visible distortions caused by compression, • No delays in video transmission, • No delays in mouse control operations • Designed to continuous operation 24/7	...	Range : ~ 10 cm ,
Power supply	5 V DC / 1 A (included)
Manufacturer / Brand	...	ENERGIZER	ATLO	...	LEGRAND	AG TERMOPASTY

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Operation temp	-20 °C ... 60 °C
Permissible relative humidity	0 % ... 90 % (non-condensing)
Weight	0.12 kg	0.001 kg	0.005 kg	0.1 kg	0.142 kg	0.1 kg
Dimensions	85 x 75 x 20 mm - Transmitter or receiver dimensions	Ø 11.6 x 4.2 mm	86 x 54 x 0.8 mm	...	85 x 85 x 78 mm	Ø 38 x 165 mm
Guarantee	2 years	2 years	2 years	2 years	2 years	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00