



	<a href="#">IP CAMERA IPC3618LE-ADF28K-G - 8.3 Mpx 4K UHD 2.8 mm UNIVIEW</a>	<a href="#">PROXIMITY READER WITH KEYPAD SO-MF5-W SATEL</a>
		
	242.90 GBP 242.90 GBP	101.63 GBP 101.63 GBP
Standard	TCP/IP	...
Sensor	1/2.7 " Progressive Scan CMOS	...
Matrix size	8.3 Mpx	...
Scanning system	Progressive	...
Cards support	...	13.56 MHz S50 : Ultralight CSN/SSN, Classic CSN/SSN/MSN, DESFire (EV1 / EV2 / EV3) CSN/MSN
Reading distance of prox-keys	...	max. 5 cm
Relay output	...	1 pcs
Relay contacts rating (resistive load)	...	1 A / 30 V
Keyboard built-in	...	✓
Autonomous operation	...	✓
Operation modes	...	<ul style="list-style-type: none"> <li>• Partition keypad in the INTEGRA alarm system</li> <li>• The keypad with proximity card reader in the ACCO NET or ACCO access control system</li> <li>• Wiegand Reader</li> <li>• standalone door control module</li> </ul>
Resolution	3840 x 2160 - 8.3 Mpx 4K UHD , 3072 x 1728 - 5.3 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p	...
Doorbell button	...	F1 button
Lens	2.8 mm	...
Tamper output	...	✓
View angle	<ul style="list-style-type: none"> <li>• 101 ° (manufacturer data)</li> <li>• 97 ° (our tests result)</li> </ul>	...
Communication	...	<ul style="list-style-type: none"> <li>• Wiegand 26-66bit</li> <li>• Open Supervised Device Protocol (OSDP)</li> <li>• RS-485</li> </ul>
Range of IR illumination	30 m	...
S/N ratio	> 56 dB	...
RS-485 interface	—	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Main features	...	<ul style="list-style-type: none"> <li>• Tamper protection (detection of removing from mounting surface and enclosure opening)</li> <li>• LED indication</li> <li>• Beep signal</li> <li>• Manual or computer programming</li> <li>• Keypad backlight buttons</li> </ul>
Average current consumption	...	65 mA
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	...
Alarm inputs / outputs	—	...
Operation temp	...	25 °C ... 55 °C
Permissible relative humidity	...	max. 93 %
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio transmission via network</li> <li>• Audio detection</li> </ul>	...
Main stream frame rate	20 fps @ 8.3 Mpx 25 fps @ 5.3 Mpx	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL / TLS, IEEE 802.1x, SNMP	...
WEB Server	Built-in	...
Max. number of on-line users	32	...
ONVIF	✓	...
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EZView</a></li> <li>• iOS (iPhone): Free application <a href="#">EZView</a></li> </ul>	...
Default IP address	DHCP or 192.168.1.13	...
Default admin user / password	admin / 123456	...
Web browser access ports	80, 554	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>	...
Mobile client access ports	80	...
Port ONVIF	80	...
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	...

Main features	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Mirror - Mirror image</li> <li>• Privacy zones - max. 4</li> <li>• Motion detection with human/vehicle silhouette recognition</li> <li>• Sharpness - sharper image outlines</li> <li>• Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion (human silhouette)</li> </ul>	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 380 mA</li> </ul>	12 V DC
Power consumption	≤ 4.5 W	...
Housing	Dome, Metal + Plastic	...
Color	White	White
"Index of Protection"	IP67	IP67
Vandal-proof	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.36 kg	0.09 kg
Dimensions	Ø 118 x 95 mm	128 x 45 x 21 mm
Supported languages	Polish, English, Czech, Spanish, French, German, Portuguese, Slovak, Hungarian, Italian	...
Manufacturer / Brand	UNIVIEW	SATEL
Guarantee	3 years	2 years