



	POWER DISTRIBUTION UNIT ACAR-504/WF/RACK	OVERVOLTAGE LIMITER AXON-MULTINET-24 ETHERNET RACK
		
	36.25 EUR 36.25 EUR	366.02 EUR 366.02 EUR
Sockets type	...	24 x RJ-45 (8-pin, 4 pairs)
Rated current	10 A (total)	...
Protected pairs of wires	...	1-2, 3-6, 4-5, 7-8
Response time	< 25 ns	...
Rated voltage	230 V AC	20 V
Maximal voltage	...	25 V
Nominal voltage of surge suppressor	250 V / 50 Hz	...
Voltage protection level (line-line)	...	40 V
Protection level of surge suppressor	≤ 1.3 kV (L/N)	...
Voltage protection level line-PG	...	600 V
Nominal discharge current (line-line)	...	100 A (8/20μs)
Nominal discharge current (line-PG)	...	100 A (8/20μs)
Nominal stroke current	2.5 kA (L/N) - 8/20 μs	...
Maximal discharge current (line-line)	...	135 A (8/20μs)
Maximal discharge current (line-PG)	...	135 A (8/20μs)
Maximum stroke current	6.5 kA (L/N) - 8/20 μs	...
Capacity	...	20 pF
Leak current	< 0.5 mA	...
Number of outlets	5 grounded outlets 10A/250V	...
Switch	two-way, with light indication	...
Length of the cable	2.7 m	...
Housing	RACK 19", 1U, Plastic - non-flammable	...
Dimensions	383 x 58 x 55 mm	490 x 85 x 44 mm
Weight	0.59 kg	1.5 kg
Guarantee	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00