

	EXPANSION PLUG KS-12/8X80 KLIMAS	EXPANSION PLUG KS-14/10X100 KLIMAS	RFID PROXIMITY CARD WITH MODIFIED UID ATLO-115	EXPANSION PLUG KW-6/3.5X35 KLIMAS	EXPANSION PLUG KW-10/6X80 KLIMAS	MONITOR DESK MOUNT BRATECK-LDT66-C01	LED STRIP CABLE AD. TL-6498/RGB/2.5M 23 m ORNO	TV OR MONITOR MOUNT AX-FLEXL25	VIDEO SEPARATOR D. SEP2/HD
									
	0.29 GBP 0.29 GBP	0.55 GBP 0.55 GBP	1.82 GBP 1.82 GBP	0.05 GBP 0.05 GBP	0.18 GBP 0.18 GBP	7.62 GBP 7.62 GBP	11.87 GBP 11.87 GBP	3.38 GBP 3.38 GBP	5.23 GBP 5.23 GBP
Standard	Unique EM 125kHz
Length of the cable	25 m
Compatibility	EM4100/4102
Possibility of programming the serial number (ID)	✓
Mounting standard	VESA 100 x 100, 75 x 75	...	VESA 75, 100	...
Ability to write to internal memory	330 bit
Material	• Expansion plug, Polypropylene • Screw, Steel galvanized	• Expansion plug, Polypropylene • Screw, Steel galvanized	...	• Expansion plug, Polypropylene • Screw, Steel galvanized	• Expansion plug, Polypropylene • Screw, Steel galvanized
Serial Number overprint	---
Drilling diameter	12 mm	14 mm	...	6 mm	10 mm
Screen size range	17" ... 32"	...	10" ... 25"	...
Expansion plug length	60 mm	80 mm	...	30 mm	60 mm
Bearing capacity	9 kg	...	15 kg	...
Distance from mounting surface	59 mm	...
Inner conductor	4 x Ø 0.35 mm - Stranded wire
Color	Black	...	Black	...
Screen dimensions	Ø 8 x 80 mm, SW-13	Ø 10 x 100 mm, SW-17	...	Ø 3.5 x 35 mm, PZ-2	Ø 6 x 80 mm, PZ-3
Tilt adjustment	45° ... 45°	...	0° ... 15°	...
Standard	• AHD - 8 Mpx, 4K UHD • HD-CVI - 8 Mpx, 4K UHD • HD-TVI - 8 Mpx, 4K UHD • CVBS - PAL / NTSC
Outer coating	4 x Ø 1.6 mm - PVC
Device type	Passive
Horizontal rotation	90° ... 90°	...	45° ... 45°	...
Number of inputs	1 pcs BNC socket
Application	• Concrete • Solid clay brick • Solid sand-lime brick	• Concrete • Solid clay brick • Solid sand-lime brick • Natural stone	...	• Concrete • Solid clay brick • Solid sand-lime brick	• Concrete • Solid clay brick • Solid sand-lime brick	...	LED strips - RGB
Rotation in the plane of the screen	360°	...	---	...
Main features	• Range : ~ 10 cm, • The T5577 chip, • The ability to save and modify additional information	Mount tube length 39.5 cm	For indoor use
Number of outputs	1 pcs BNC plug
Input impedance	75 Ω
Output impedance	75 Ω
Coating color	Black + Green + Red + Blue
Opto-isolation between inputs and outputs	16 V DC
Manufacturer / Brand	KLIMAS	KLIMAS	ATLO	KLIMAS	KLIMAS	BRATECK	ORNO
Attenuation	• 4.43 MHz @ 0.21 dB • 11 MHz @ 0.41 dB • 21 MHz @ 0.82 dB • 38 MHz @ 1.19 dB • 42 MHz @ 1.17 dB • 67.5 MHz @ 3.46 dB
Insertion loss	0.5 dB
Bandwidth	180 MHz
Power supply	---
Operation temp	-20 °C ... 55 °C
Weight	0.01 kg	2.1 kg	...	0.31 kg	0.03 kg
Dimensions	86 x 54 x 2 mm	507 x 308 x 117 mm	...	130 x 120 x 59 mm	60 x 28 x 22 mm
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00