




	CLEANING PASTE PEVALIN-PROFESSIONAL/250 TUBE 250 ml TESA	IP HYBRID THERMAL IMAGING CAMERA TPC-BF2241-TB7F8-S2 7.0 mm - 960p, 8.0 mm - 4 Mpx DAHUA	CONNECTOR FOR LED STRIPS AD-TL-6499/Z/L/RGB 10 mm ORNO
			
	12.99 AUD 12.99 AUD	3397.64 AUD 3397.64 AUD	1.29 AUD 1.29 AUD
Package	Tube 250 ml
Application	Works with LED lighting RGB
Strip width	10 mm
Pixel pitch	...	12 µm	...
Thermal sensitivity (NETD)	...	< 40 mK @ F1.0	...
Maximal power voltage	48 V
Spectral range	...	8 µm ... 14 µm	...
Color palettes	...	18	...
Sensor	...	Uncooled VOx microbolometer 1/2.7 " Progressive Scan CMOS	...
Matrix size	...	256 x 192 px 4 Mpx	...
Lens	...	7.0 mm 8.0 mm	...
View angle	...	24 ° 33.4 °	...
Optical zoom	...	—	...
Digital zoom	...	—	...
Min. illumination	...	0.05 Lux (color) @ F2.0 0.005 Lux (B/W) @ F2.0	...
Range of IR illumination	...	50 m	...
Resolution	...	1280 x 960 - 960p , 1024 x 768 px , 640 x 480 px , 256 x 192 px 2336 x 1752 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p 704 x 576 - 4CIF 352 x 288 - CIF	...
Standard	...	TCP/IP, CVBS	...
Video output	...	CVBS - 1 Vpp / 75 Ω, BNC	...
RS-485 interface	...	✓	...
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)	...
Image compression method	...	H.265 / H.264 / H.264H / H.264B / MJPEG	...
Alarm inputs / outputs	...	1 / 1	...
Audio	...	• Audio input • Audio output • Bi-directional audio streaming support	...
Main stream frame rate	...	25 fps @ 1280 x 960 25 fps @ 4 Mpx	...
Network interface	...	10/100 Base-T (RJ-45)	...
Network protocols	...	HTTPS, HTTP, TCP, ARP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/IPv6, SNMP, QoS, UPnP, NTP	...
WEB Server	...	Built-in, NVR compliance	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Max. number of on-line users	...	10	...
ONVIF	...	✓	...
Mobile phones support	...	Port 37777 • Android: Free application DMSS • iOS (iPhone): Free application DMSS	...
Default IP address	...	192.168.1.108	...
Default admin user / password	...	admin / - The administrator password should be set at the first start	...
Web browser access ports	...	80, 37777	...
PC client access ports	...	37777	...
Mobile client access ports	...	37777	...
Port ONVIF	...	80	...
RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Main features	...	<ul style="list-style-type: none"> • The possibility of overlapping the image from a thermal imaging camera in a classic image - 3 Display modes • PIP - Picture In Picture • D-WDR - Wide Dynamic Range • ROI - improve the quality of selected parts of image • EIS - Electronic Image Stabilization • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • WB - White Balance (ATW/AWB/manual/indoor/outdoor) • Motion Detection • Temperature measurement in the range: -20°C ... +550°C • Intelligent tracking of warmest / coldest point • IVS analysis : crossing the line (tripwire), intrusion, object detection (people, vehicle), fire detection, Smoke detection • Active deterrence function - Light and sound alarm • 6kV protection of the camera and its structure against the effects of lightning • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 8 / 15 kV 	...
Housing	...	Compact - Metal	...
Color	...	White	White
"Index of Protection"	...	IP67	—
Power supply	...	<ul style="list-style-type: none"> • ePoE, • PoE (802.3af), • 12 V DC / 1 A 	...
Power consumption	...	≤ 12 W	...
Operation temp	...	-30 °C ... 60 °C	...
Weight	...	1.4 kg	0.002 kg
Dimensions	...	96 x 104 x 280 mm	20 x 20 mm
Supported languages	...	English	...
Manufacturer / Brand	TESA	DAHUA	ORNO
Guarantee	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00