





	ELECTRIC CABLE YKY-5X4.0	WIRELESS TWO-CHANNEL 230V AC CONTROLLER ASW-210 (Smart 2-CH Relay) ABAX/ABAX2 SATEL	UPS COVER-CORE-1K 1000 VA COVER
			
	15.68 PLN 15.68 PLN	183.00 PLN 183.00 PLN	1670.25 PLN 1670.25 PLN
Power adapter type	Online
Nominal power	900 W
Apparent Power	1000 VA
In section	100 m . Price for 1m when buying a whole roll
Inner conductor	5 x 4.0 mm ² - Cu wire
Input voltage	208 V / 220 V / 230 V / 240 V AC
Rated voltage	0.6 / 1 kV
Support	...	ABAX/ABAX2 • ACU-220, ACU-280, ARU-200 • Cooperation available soon ... : ACU-120, ACU-270, INTEGRA-128-WRL, ARU-100	...
Outer coating	Ø 15.5 mm - PVC
Number of control inputs	...	2 pcs	...
Coating color	Black
Input frequency	50 / 60 Hz @ -20 % / +20 %
Output voltage	208 V / 220 V / 230 V / 240 V AC (Pure Sine Wave)
Main features	...	<ul style="list-style-type: none"> • The ASW-210 module is intended for remote switching on and off of devices powered from the 230V AC mains, • The control inputs are designed for connecting, for example, wall switches (mono and bistable), • Remote configuration, • Remote update of module software 	...
Power factor	0.9
Output frequency	50 / 60 Hz ± 0.05 Hz
Voltage adjustment	✓
Frequency adjustment	✓

Charging time (recover to 90% capacity)	4 hours
Battery	3 x 12V/9Ah
Estimated battery operation time	<ul style="list-style-type: none"> • 43 minutes @ 450 W, • 73 minutes @ 675 W, • 32 minutes @ 900 W
Number of outputs	8 pcs IEC-320 C13
Management software	ViewPower
Protections	<ul style="list-style-type: none"> • Short-circuit • Overload • Overcharge protection • discharge protection • Output voltage filtering • EPO (Emergency power off) switch
Operation state indication	<ul style="list-style-type: none"> • LCD display: operation mode, battery charging level, in/out voltage level, overload indicator, • Sound signaling
Main features	<ul style="list-style-type: none"> • Auto restart while AC is recovering • Automatic bypass • The device has a rotating display • COLD START function for manual switch to the battery power supply • Battery charge and maintenance control • Port RS-232 - Access from PC • Remote management - ViewPower application (included) • Battery replacement during operation (Hot-swap) • Network card slot • Can be mounted in a Rack 19" cabinet
Application	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type	Rack/Tower 2-in-1 Design
Operation temp. / Relative humidity	0 °C ... 45 °C / 0 ~ 95 % (non-condensing)
Weight	...	0.04 kg	15.3 kg
Dimensions	...	47 x 47 x 21 mm	438 x 428 x 88 mm ; RACK 19", 2U

Manufacturer / Brand	...	SATEL	COVER
Guarantee	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00