





	ACCESS CONTROLLER ASI3213G-MW DAHUA	EXTENDER ETHERNET VIA UTP CABLE EA-EOU101 COP	EXTENDER ETHERNET+PoE LR1002-1ET-V3 TRANSMITTER DAHUA	ISOPROPYL ALCOHOL KONTAKT-IPA-PLUS/5000 METAL CANISTER 5 l AG TERMOPASTY
				
	495.39 EUR 495.39 EUR	77.66 EUR 77.66 EUR	26.41 EUR 26.41 EUR	28.88 EUR 28.88 EUR
LAN ports	...	1 pcs RJ45	1 pcs RJ45	...
Sensor	CMOS
Package	Metal canister 5 l
Matrix size	2 Mpx
Application	Ideal for removing dirt from optical components
Transmission ports	...	1 pcs BNC + BNC / UTP converter - cable terminals	1 pcs BNC	...
Transmission speed	...	10 / 100 Mbps Full Duplex	10 / 100 Mbps	...
Resolution	1920 x 1080 - 1080p
Transmission range	...	max. 1000 m	max. 1000 m @ 10 Mbps max. 400 m @ 100 Mbps The range of data transfer and power supply is strongly dependent on the cable used and the power required to supply the receiver	...
Protections	Overvoltage	...
Standard	TCP/IP
IR illuminator	✓
LED illuminator	✓
Main features	...	<ul style="list-style-type: none"> • Plug & Play • The device uses 1 pair of twisted-pair cable for transmission to 1 IP camera 	<ul style="list-style-type: none"> • Plug & Play • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Support for IP cameras and network devices • Easy installation - doesn't require any configuration of IP nor MAC address • Power supply PoE - pins 1, 2 and 3, 6 • The device operates from the camera side • Possibility to mount on a wall, or on the DIN TS-35 rail • UTP cable length to the camera max. 2 m 	...
Temperature measurement	—

Temperature measurement range	—
Accuracy of temperature measurement	—
Face recognition distance	0.3 m ... 1.5 m (max 1500 faces in the database)
RFID proximity reader built-in	<ul style="list-style-type: none"> • 13.56 MHz S50 • Memory of 1500 RFID cards
Internal memory	Support storage of 150 000 records
Video output	—
RS-485 interface	✓
RS-232 interface	—
Wiegand interface	—
USB	1 x USB 2.0
Memory card slot	—
Alarm inputs / outputs	1 / 1 - Relay outputs
Audio	Voice message
Network interface	1 x 10/100 Base-T (RJ-45)
Network protocols	IPv4, RTSP, RTP, TCP, UDP, P2P
WEB Server	Built-in
ONVIF	—
Default IP address	192.168.1.108
Default admin user / password	admin / - The administrator password should be set at the first start
Web browser access ports	80, 37777
PC client access ports	37777



Main features	<ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera - 4.3 " capacitive touch screen, 480 x 272 px • Identification modes : PIN, Proximity identifier 13.56 MHz S50, Face recognition, Any combination of the above • 1500 users • Software update via network • Real-time Surveillance • Multiple Authentication • Take face image after swiping card • Auto-Registration • Backup to USB drive (pendrive, external drive) • Output button support • Door status detection • Lock control • Function to prevent of multiple use of the same code/card to gain access (anti-passback) • Auto-uploads alarm messages to Master or client station after entering the duress code to open the door • Ability to work with reed switch and signalling the door being opened too long • 128 General Purpose Schedules • Unlocking the transition only when more than one user is present • Tamper protections
Power supply	12 V DC / 1.5 A (power adapter included)	12 V DC / 500 mA (power adapter included)	<ul style="list-style-type: none"> • ePoE • PoE (802.3af/at) 	...
Power consumption	≤ 18 W
Housing	Plastic (ABS)
Color	Black + Silver
"Index of Protection"	—
Operation temp	-10 °C ... 55 °C
Weight	<ul style="list-style-type: none"> • 0.22 kg (without stand) • 0.24 kg (with stand) 	0.14 kg	0.07 kg	4.371 kg
Dimensions	<ul style="list-style-type: none"> • 116 x 107 x 22 mm (without stand) • 116 x 107 x 78 mm (with stand) 	120 x 33 x 33 mm	79 x 64 x 23 mm	315 x 168 x 105 mm
Supported languages	English
Manufacturer / Brand	DAHUA	COP	DAHUA	AG TERMOPASTY
Guarantee	3 years	2 years	3 years	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00