



| | | |
|-----------------------------------|---|--|
| | ACCESS CONTROL PANEL CPR32-NET-BRD ROGER | KRONE BACK-MOUNT FRAME LSA-GN-10/3 |
| |  |  |
| | 321.87 EUR 321.87 EUR | 1.86 EUR 1.86 EUR |
| Number of mounted profile modules | ... | 3 pcs |
| Type of mounted profile modules | ... | 10PAR |
| Inputs | <ul style="list-style-type: none"> • 8 pcs - Mainboard inputs • max. 32 | ... |
| Outputs | <ul style="list-style-type: none"> • 6 pcs - Transistor outputs • 2 pcs - Relay outputs NO/NC | ... |
| Communication | <ul style="list-style-type: none"> • 2 x RS-485 | ... |
| Events memory | <ul style="list-style-type: none"> • Events saving to the micro SD card (not included) • Recording up to 240 000 events from the control panel | ... |
| Output load | <ul style="list-style-type: none"> • Transistor outputs : 1 A / 15 V DC • Relay outputs : 1.5 A / 30 V DC | ... |
| Main features | <ul style="list-style-type: none"> • Ability to block/unblock partition at a specified time, or as per access schedule, • Central management of the access control system, • Integration with the alarm system SATEL INTEGRA, • History of 250 000 events • Electrical protection of all inputs and outputs as well as communication buses • Full support via network | ... |
| Power supply | <ul style="list-style-type: none"> • 24 V DC • 12 V DC • 18 V AC | ... |
| Battery backup support | ✓ | ... |
| Operation temp | 5 °C ... 40 °C | ... |
| Permissible relative humidity | 10 % ... 95 % (non-condensing) | ... |
| Dimensions | 175 x 81 x 50 mm | 67 x 112 x 50 mm |
| Weight | 0.15 kg | ... |
| Manufacturer / Brand | ROGER | ... |
| Guarantee | 3 years | 2 years |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00