

	<a href="#">POWER DISTRIBUTION UNIT LE-049484 (6 OUTLETS) 1.5 m LEGRAND</a>	<a href="#">REPAIRING TAPE DUCT-TAPE-PRO/50X50/S TESA</a>	<a href="#">RACK CABINET LOCK A19: LOCK-N</a>	<a href="#">BLANK PANEL TO RACK CABINET Z19-4U*P2</a>	<a href="#">NVR NVR302-08E2-P8-IO 8 CHANNELS, 8 PoE UNIVIEW</a>
					
	67.66 PLN 67.66 PLN	37.75 PLN 37.75 PLN	7.92 PLN 7.92 PLN	44.93 PLN 44.93 PLN	3145.15 PLN 3145.15 PLN
Application	...	...	EPRADO BLUE	...	...
Standard	...	...	...	...	TCP/IP
Length	...	50 m	...	...	...
Thread type	...	...	M18	...	...
Thickness	...	0.175 mm	...	...	...
Rated voltage	230 V AC / 50 Hz	...	...	...	...
Bolt length	...	...	26 mm	...	...
Supported resolutions	...	...	...	...	max. 12 Mpx - 4000 x 3000 px
Total maximal current	16 A	...	...	...	...
Distance of the bolt from the lock	...	...	16 mm	...	...
In package	...	...	...	<b>2 pcs The price for package</b>	...
Maximal total load	3680 W	...	...	...	...
Width	...	50 mm	...	19 "	...
Video outputs	...	...	...	...	1 pcs HDMI 4K 1 pcs VGA
Height	...	...	...	4 U	...
Material	...	PE + PET	...	...	...
Number of outlets	6 grounded outlets 16A/250V CEE 7/5	...	...	...	...
Material	...	...	Zinc alloy	Steel - powder painted	...
Fuse	—	...	...	...	...
Audio support	...	...	...	...	• 8 Channels - Audio from cameras • Bi-directional audio streaming support
Switch	—	...	...	...	...
Audio inputs	...	...	...	...	1 pcs CINCH
Wire gauge	3 x 1.0 mm <sup>2</sup>	...	...	...	...
Audio outputs	...	...	...	...	1 pcs CINCH
Length of the cable	1.5 m	...	...	...	...
Housing	Plastic	...	...	...	...
Color	White / Gray	Gray	...	Black	...
Image compression method	...	...	...	...	Ultra 265 / H.265 / H.264
Bitrate	...	...	...	...	max. 320 Mbps
Supported hard drives	...	...	...	...	2 x 10 TB SATA
Main features	...	<ul style="list-style-type: none"> <li>Reinforcing mesh,</li> <li>Elongation at break : 14 %</li> <li>Tensile strength : 40 N/cm</li> <li>Adhesion to steel : 7 N/cm</li> <li>Adhesion to rough surfaces : 5.5 N/cm</li> </ul>	2 keys included	...	...
Recording modes	...	...	...	...	Manual, Sensor, Motion detection, Schedule
External storage devices backup	...	...	...	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	...	...	...	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4/6/8/9 channel synchronous playback
Network interface	...	...	...	...	1 x RJ-45 10/100/1000 Base-TX
Network functions	...	...	...	...	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Network protocols	...	...	...	...	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS
ONVIF	...	...	...	...	✓
Default IP address	...	...	...	...	DHCP or 192.168.1.30
Default admin user / password	...	...	...	...	admin / 123456
Mobile phones support	...	...	...	...	Port no.: 80 or access by a cloud (P2P) • Android: Free application <a href="#">EZView</a> • iOS (iPhone): Free application <a href="#">EZView</a>
Web browser access ports	...	...	...	...	80, 554
PC client access ports	...	...	...	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>
Mobile client access ports	...	...	...	...	80
RTSP URL	...	...	...	...	rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream
USB	...	...	...	...	1 x USB 2.0 1 x USB 3.0
Serial ports	...	...	...	...	RS-485
Alarm inputs / outputs	...	...	...	...	8 / 2
PTZ control	...	...	...	...	• PTZ Uniview cameras • RS-485 control
Motion Detection	...	...	...	...	✓
Intelligent image analysis	...	...	...	...	✓
Main features	...	...	...	...	• Motion detection with human/vehicle silhouette recognition • Filtering of false alarms based on the recognition of persons and vehicles (tripwire, intrusion)
Mouse support	...	...	...	...	✓
IR remote controller in the set	...	...	...	...	—
Switch PoE	...	...	...	...	16-port PoE Switch built-in, 30 W / Channel, PoE (802.3af/at)
Maximum total switch load	...	...	...	...	130 W
Power supply	...	...	...	...	100 ... 240 V AC
Power consumption	...	...	...	...	max. 15 W (without HDD)
Operation temp	...	...	...	...	-10 °C ... 55 °C
Weight	0.39 kg	...	0.04 kg	0.9 kg	2.48 kg
Dimensions	295 x 54 x 37 mm	...	47 x 28 x 23 mm	...	380 x 322 x 53 mm
Supported languages	...	...	...	...	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian
Manufacturer / Brand	LEGRAND	TESA	EPRADO	...	UNIVIEW
Guarantee	2 years	2 years	2 years	2 years	3 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00