



	<a href="#">SWITCH TL-SG3424 24-PORT + SFP TP-LINK</a>	<a href="#">3 PCS SET ACCESS POINT +ROUTER MAXI8-3 Wi-Fi 6 2.4 GHz, 5 GHz DAHUA</a>	<a href="#">THERMALLY CONDUCTIVE ADHESIVE TERM-GLUE/120 TUBE 120 g AG THERMOPASTY</a>	<a href="#">FURNITURE POWER DISTRIBUTION UNIT FS-18 (3 OUTLETS) 1.8 m Virene</a>	<a href="#">RFID PROXIMITY CARD ATLO-D194</a>	<a href="#">HIGH POE POWER ADAPTER TAM01GT01GT-75 - 75 W DAHUA</a>	<a href="#">TV OR MONITOR MOUNT BRATECK-PLB-6N</a>
							
	198.84 CHF 198.84 CHF	187.00 CHF 187.00 CHF	20.58 CHF 20.58 CHF	25.53 CHF 25.53 CHF	0.63 CHF 0.63 CHF	51.06 CHF 51.06 CHF	15.89 CHF 15.89 CHF
Rated voltage	...	...	...	230 V AC / 50 Hz	...	...	...
Package	...	...	Tube 120 g	...	...	...	...
Total maximal current	...	...	...	16 A	...	...	...
In package	...	<b>3 pcs</b>	...	...	...	...	...
Standard	...	...	...	...	...	• 13.56 MHz S50, • Unique EM 125kHz	...
Maximal total load	...	...	...	3680 W	...	...	...
Input voltage	...	...	...	...	...	100 ... 240 V AC	...
Compatibility	...	...	...	...	...	...	...
Frequency range	...	2.4 GHz, 5 GHz	...	...	ISO/IEC 14443A	...	...
Output voltage	...	...	...	...	...	53 V DC	...
Possibility of programming the serial number (ID)	...	...	...	...	...	---	...
Number of outlets	...	...	...	3 grounded outlets 16A/250V CEE 7/5, E type	...	...	...
Maximal output current	...	...	...	...	...	1.42 A	...
Ability to write to internal memory	...	...	...	...	...	---	...
Fuse	...	...	...	---	...	---	...
Number of inputs	...	...	...	...	...	1 pcs RJ-45	...
Serial Number overprint	...	...	...	...	...	---	...
Switch	...	...	...	---	...	---	...
Wire gauge	...	...	...	3 x 1.5 mm <sup>2</sup>	...	---	...
Mounting standard	...	...	...	...	...	...	VESA 75, 100, 150, 200, 200x100, 300, 400, 400x200
Length of the cable	...	...	...	1.8 m	...	...	...
Antenna type	...	• 2.4 GHz : 2 x pcs Omnidirectional antenna - built-in • 5 GHz : 2 x Omnidirectional antenna - built-in	...	...	...	...	...
Connector	...	...	...	...	...	• 1 x RJ-45 socket - Input • 1 x RJ-45 socket - Output	...
Screen size range	...	...	...	...	...	...	26 " ... 47 "
Bearing capacity	...	...	...	...	...	...	75 kg
Distance from mounting surface	...	...	...	...	...	...	77 mm
LED indicators	...	...	...	...	...	Power, PoE	...
Tilt adjustment	...	...	...	...	...	...	-15 ° ... 15 °
Housing	...	...	...	Plastic + Aluminum	...	...	...
"Index of Protection"	...	...	...	IP20	...	...	...
Standards	...	• LAN : IEEE 802.3 IEEE 802.3u, IEEE 802.3ab, • Wi-Fi : IEEE 802.11 b/g/n/ac/ax	...	...	...	High PoE - 75 W	...
Supported data rates	...	...	...	...	...	• Supported data rates 10 / 100 / 1000 Mbps - Gigabit Ethernet, • Midspan mode support	...
Color	...	...	White	Black + Silver	...	...	Black
Output power	...	...	...	...	...	75 W	...
Baud rates	...	574 Mbps + 1201 Mbps	...	...	...	...	...
Protections	...	WPA2	...	...	...	...	...
LAN ports	Switch is managed via a web browser, command line interface and SNMP, RMON protocols • 24 x RJ45, • 4 x port SFP - Uplink, • 1 x RJ45 - Console	3 x 10/100/1000 Mbps	...	...	...	...	...
Management	✓	...	...	...	...	...	...
Transmission speed	• 10 / 100 / 1000 Mbps - 24 LAN ports, • 100 / 1000 Mbps - 4 SFP ports	...	...	...	...	...	...
Power consumption	...	≤ 12 W	...	...	...	...	...
Jumbo Frame	10240 B	...	...	...	...	...	...
MAC addresses table	8k	...	...	...	...	...	...
Operation temp	...	-10 °C ... 55 °C	...	...	...	-30 °C ... 65 °C	...
Permissible relative humidity	...	5 % ... 95 %	...	...	...	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> <li>Switch is managed via a web browser, command line interface and SNMP, RMON protocols</li> <li>CoS/DSCP priority based on IEEE 802.1p standard</li> <li>Queue scheduling: SP, WRR, SP+WRR</li> <li>Port/flow-based rate limiting</li> <li>IEEE 802.1Q VLAN, Port Based VLAN, MAC Based VLAN, Private VLAN support</li> <li>IEEE 802.1Q standard support, up to 4096 VLAN groups and 4K VIDs</li> <li>IGMP Snooping V1/V2/V3</li> <li>Spanning Tree STP/RSTP/MSTP</li> <li>BPDU Filtering/Guard</li> <li>TC / Root Protect</li> <li>Loop back detection</li> <li>Data Flow Control (802.3x)</li> <li>IP-MAC-Port-VID Binding</li> <li>Access Control List - L2/L4 ACL package filtering based on source and destination MAC addresses</li> <li>IEEE 802.1x and Radius Authentication</li> <li>Support DoS defence</li> <li>Port Security</li> <li>IPv6 compliance</li> <li>SSL, SSH</li> </ul>	<ul style="list-style-type: none"> <li>Support for Mesh technology,</li> <li>Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments</li> <li>Port Security : Contact/Air (ESD/EMP) <math>\pm 8</math> kV / <math>\pm 6</math> kV</li> <li>Easy and uniform management system for many devices - WiLynk application</li> <li>Intuitive installation and configuration of many advanced functions</li> </ul>		<ul style="list-style-type: none"> <li>Fixing in the opening of the table top <math>\varnothing 82</math> mm</li> <li>PDU pulled out from the table top</li> <li>Outlets protected with a protection shutter</li> </ul>	Range : ~ 10 cm ,	Meets the requirements of DoE level VI	
LED diodes	Power, Link/Act, System, 1000 Mbps Console	...	...	...	...	...	...
Certificates	CE	...	...	...	...	...	...
Power supply	100 ... 240 V AC	12 V DC / 1.5 A (power adapter included)	...	...	...	...	...
Weight	3.02 kg	0.23 kg	...	0.67 kg	0.005 kg	0.48 kg	3.11 kg
Dimensions	440 x 220 x 44 mm, RACK 19", 1U	95 x 95 x 73 mm	...	$\varnothing 106$ x 284 mm	86 x 54 x 0.8 mm	210 x 75 x 38 mm	516 x 508 x 77 mm
Manufacturer / Brand	TP-LINK	DAHUA	AG TERMOPASTY	Virone	ATLO	DAHUA	...
Guarantee	5 years	2 years	2 years	2 years	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00