






	WIRELESS VIDEO DOORPHONE ATLO-DBC52-TUYA Wi-Fi, Tuya Smart	ACCESS POINT 4G+ LTE Cat. 6 +ROUTER LTE-CA2-103 Wi-Fi 2.4 GHz, 5 GHz, 866 Mbps + 300 Mbps	3 PCS SET ACCESS POINT +ROUTER MAX18-3 Wi-Fi 6, 2.4 GHz, 5 GHz DAHUA	HUB USB 2.0 Y-2140 80 cm	TRIPLE SMART LIGHT SWITCH ATLO-WB3/K-TUYA Wi-Fi, Tuya Smart
					
	96.23 EUR 96.23 EUR	109.16 EUR 109.16 EUR	191.88 EUR 191.88 EUR	4.68 EUR 4.68 EUR	10.54 EUR 10.54 EUR
Application	Works with lighting - switching on/off
Sensor	SmartSens CMOS - 2 Mpx
In package	3 pcs
Connectors	• 1 x plug - USB-A • 4 x socket - USB-A	...
Resolution	1920 x 1080 px - 1080p
Length of the cable	80 cm	...
Rated voltage	100 ... 240 V AC, 50 / 60 Hz
USB standard	2.0	...
Lens	2.0 mm F1.2
View angle	140 °
Maximum power	600 W (for each output)
Rated current	max. 10 A
Number of buttons	3
Number of outputs	3
IR illuminator	5 ... 10 m
Connector type	screw terminals
LED illuminator	—
proximity reader built-in	Unique EM 125kHz
Wireless transmission range	The range limited only by the availability of the Wi-Fi network
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Wi-Fi standard	2.4 GHz IEEE 802.11 b/g/n
Frequency range	...	• Wi-Fi : 2.4 GHz, 5 GHz, • LTE : 2600 MHz, 2500 MHz, 2300 MHz, 2100 MHz, 1800 MHz, 900 MHz, 850 MHz, 800 MHz, 700 MHz	2.4 GHz, 5 GHz
Network interface	• 10/100 Mbps Fast Ethernet, RJ-45 socket • 2.4 GHz Wi-Fi
Antenna type	...	• 4 x Omnidirectional antenna Wi-Fi, Integrated, • 2 x Omnidirectional antenna 4G LTE, Integrated	• 2.4 GHz : 2 x pcs Omnidirectional antenna - built-in • 5 GHz : 2 x Omnidirectional antenna - built-in
Mobile phones support	The Tuya Smart free application on Android The Tuya Smart free application on iOS	• The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Standards	...	IEEE 802.11 b/g/n/ac	• LAN : IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, • Wi-Fi : IEEE 802.11 b/g/n/ac/ax
Image compression method	H.265 / H.264
Supported audio formats	G.711

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Baud rates	...	• Wi-Fi : 866 Mbps + 300 Mbps, • LTE Cat. 6 : 300 Mbps / 50 Mbps	574 Mbps + 1201 Mbps
Power consumption	≤ 12 W
LAN ports	...	1 x 10/100/1000 Mbps - Uplink / LAN 4 x 10/100/1000 Mbps - LAN	3 x 10/100/1000 Mbps
LED indicators	...	Power, SYS, LTE, Wi-Fi, 4 x Ethernet, WAN
SIM socket	...	1 x mini SIM
Permissible relative humidity	5 % ... 95 %	...	≤ 80 %
DDNS	...	✓
DHCP server	...	✓
Firmware update	...	✓
Manufacturer / Brand	DAHUA	UNITEK	...
Protections	...	WEP, WPA/WPA2, WPA-PSK/WPA2-PSK	WPA2
Management interface	...	Web browser
Transmitter power	...	< 20 dBm
Main features	...	<ul style="list-style-type: none"> Built-in 5-port switch RESET button Remote management 	<ul style="list-style-type: none"> Support for Mesh technology, Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments Port Security : Contact/Air (ESD/EMP) ± 8 kV / ± 6 kV Easy and uniform management system for many devices - WiLynk application Intuitive installation and configuration of many advanced functions 	...	<ul style="list-style-type: none"> Local control by physical button, schedule, timer, Setting scenarios by different events, remote access, voice control, LED indication



Main features	<ul style="list-style-type: none"> • ATLO-DBC5/CHIME wireless support • Possibility of expansion with an additional ATLO-DBC5/RELAY wireless relay • Micro SD memory cards up to 256GB support (possible local recording) • Various record modes - users can choose time range for recording during day and set the specific recording mode: recording from motion detection, manual recording, schedule recording, • Motion Detection, • PIR detector, • Indoor proximity cards and key-fobs reader, • ICR - Movable InfraRed filter • Day/night mode, • Microphone built-in, • Speaker built-in, • Bidirectional communication, • Noise and echo reduction • Full support via network • 5 on-line users, • Possibility to work in cloud - you don't need to redirect the ports, • Video PUSH personal messaging - Motion Detection, • Video recording - Motion Detection, Doorbell button, • Automatic events notification via Email messages • Lock control - Relay output • Tamper protections • Google Home, Amazon Echo compliance
Mount	Surface-mounted
Power supply	<ul style="list-style-type: none"> • 12 V DC / 1 A (power adapter included) • 48 V PoE (802.3af) 	12 V DC / 1 A (power adapter included)	12 V DC / 1.5 A (power adapter included)
Housing	Aluminum + Plastic (ABS)	Plastic
Color	Silver	White
"Index of Protection"	IP44
Operation temp	-20 °C ... 55 °C	...	-10 °C ... 55 °C	...	-20 °C ... 50 °C
Weight	<ul style="list-style-type: none"> • 0.22 kg - Wireless Video Doorbell • 0.046 kg - rain cover 	0.42 kg	0.23 kg	0.03 kg	0.102 kg
Dimensions	<ul style="list-style-type: none"> • 141 x 87 x 25 mm - Wireless Video Doorbell • 147 x 94 x 40 mm - rain cover 	238 x 149 x 33 mm	95 x 95 x 73 mm	65 x 23 x 19 mm	87 x 86 x 41 mm
Guarantee	2 years	2 years	2 years	2 years	2 years