





	IP CAMERA IPC-PDW5849-A180-E2-ASTE-0360B PANORAMIC Full-Color WizMind - 7.3 Mpx 2 X 3.6 mm DAHUA	POWER DISTRIBUTION UNIT PR-1.5M-3G/W (3 OUTLETS) 1.3 m	MODEM 4G LTE, MOBILE ROUTER TL-M7450 Wi-Fi 300 + 867 Mb/s TP-LINK	CAMERA BRACKET PFA120 DAHUA
				
	1023.92 EUR 1023.92 EUR	3.45 EUR 3.45 EUR	168.75 EUR 168.75 EUR	28.34 EUR 28.34 EUR
Standard	IP
Suitable for cameras	DAHUA - documentation for download below.
Material	Aluminum
Frequency range	2.4 GHz, 5 GHz	...
Rated voltage	...	220 ... 240 V AC / 50 Hz
Total maximal current	...	10 A
Distance from mounting surface	37 mm
Maximal total load	...	2500 W
Number of outlets	...	3 grounded outlets 10A/250V CEE 7/5
Fuse	...	—
Antenna type	1 x WiFi - Internal antenna , 1 x 4G LTE - Internal antenna	...
Switch	...	—
Wire gauge	...	3 x 1.5 mm ²
Length of the cable	...	1.3 m
Standards	IEEE 802.11 b/g/n - 2.4 GHz, IEEE 802.11 a/n/ac - 5 GHz, 4G LTE, 3G DC-HSPA+/HSPA/UMTS	...
Resolution	4096 x 1800 - 7.3 Mpx , 3840 x 1680 - 6 Mpx , 3840 x 1080 - 4.1 Mpx , 2880 x 1264 - 3.6 Mpx , 1920 x 832 - 1.6 Mpx
Sensor	2 x 1/1.8 " Progressive Scan CMOS
Lens	2 x 3.6 mm
View angle	180 °
White light LED illuminator range	40 m
Min. illumination	0.0005 Lux / F1.0 (color)
S/N ratio	> 56 dB
Baud rates	• LTE : 300 / 50 Mbps, • IEEE 802.11 b/g/n @ 2.4 GHz : 300 Mbps, • IEEE 802.11 a/n/ac @ 5 GHz : 867 Mbps	...
RS-485 interface	—
Memory card slot	Micro SD card support up to 512GB
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	1 / 1
Audio	• Microphone built-in, • External microphone input, • Speaker built-in • Audio output • Bi-directional audio streaming support • Audio detection
Main stream frame rate	20 fps @ 7.3 Mpx
Network type	• 4G : FDD-LTE B1/B3/B5/B7/B8/B20/B28 - 2100 / 1800 / 850 / 2600 / 900 / 800 / 700 MHz • 4G : TDD-LTE B38/B40/B41 - 2600 / 2300 / 2500 MHz • 3G : DC- HSPA+/HSPA/UMTS B1/B5/B8 - 2100 / 850 / 900 MHz	...
Network interface	10/100 Base-T (RJ-45)
LAN ports	—	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

WEB Server	Built-in
Max. number of on-line users	20
ONVIF	✓
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address	192.168.1.108
Ports	• 1 x micro USB - Battery charging • 1 x SIM socket • 1 x microSD	...
Default admin user / password	admin / - The administrator password should be set at the first start
Web browser access ports	80, 37777
PC client access ports	37777
Mobile client access ports	37777
Port ONVIF	80
RTSP URL	rtsp://admin.haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin.haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Receiver sensitivity	• 2.4 GHz 11b 11 Mbps : -86 dBm • 2.4 GHz 11g 54 Mbps : -71 dBm • 2.4 GHz 11n HT20 MCS7 : -68 dBm • 2.4 GHz 11n HT40 MCS7 : -65 dBm • 5 GHz 11a 54 Mbps : -70 dBm • 5 GHz 11n HT20 MCS7 : -68 dBm • 5 GHz 11n HT40 MCS7 : -65 dBm	...
Intelligent image analysis	• crossing the line (tripwire) - classification of people and vehicles • intrusion - classification of people and vehicles • fast moving - classification of people and vehicles • parking detection • detection of people gathering • people counting - Supports area or queue management and the ability to configure up to 4 rules
Transmitter power	< 20 dBm @ 2.4 GHz < 23 dBm @ 5 GHz	...
Main features	• EPTZ - advanced target detection and tracking algorithms that trigger alarms - can simultaneously zoom and track many people and/or vehicles • WDR - 140 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • SMD 3.0 - searching for an object classified as: human, motor vehicle • SSA - Smart Scene Adaptive - intelligent scene adaptation by automatically adjusting the exposure parameters to obtain a better image • BLC/HLC - Back Light / High Light Compensation • Day/night mode • Full Color - colorful night mode • Auto White Balance • AGC - Automatic Gain Control • Motion Detection - max. 4 zones • Privacy zones - max. 8 • Mirror - Mirror image • Light and sound alarm • White light (LED) illuminator built-in : 2 LEDs
Power consumption	• ≤ 11.8 W @ PoE • ≤ 10.5 W @ 12 V
Housing	Dome - Metal	Plastic
Color	White	White	...	White
"Index of Protection"	IP67
Mechanical protection class	—

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Operation temp	-40 °C ... 60 °C
Main features	<ul style="list-style-type: none"> • AC1200 Dual Band WiFi • ON/OFF button • MENU button • RESET button • The microSD - max. 32 GB cards support • 1.44 " Color LCD : WiFi, INTERNET, Battery charge indicator, Wireless transmission statistics, Number of users, Network type, Signal indicator, Text messages, network name, network password • Transmission encryption : WPA-PSK/WPA2-PSK • MAC addresses filtering • SSID hiding • DHCP server • DHCP client list • RNDIS support • Max. number of supported devices : 32 • Backup time max. 15 h • Remote management - tpMiFi application • System requirements : Windows XP/Vista/7/8/10, Mac OS, Android, iOS (iPhone, iPad), Windows Phone 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3at), • ePoE, • 12 V DC / 750 mA 	...	<ul style="list-style-type: none"> • 3000 mAh Battery • 5 V DC / 1 A Charging via USB port 	...
Operation temp	0 °C ... 35 °C	...
Permissible relative humidity	10 % ... 90 % (non-condensing)	...
Weight	0.97 kg	0.29 kg	0.14 kg	0.53 kg
Dimensions	Ø 122 x 132 mm	154 x 54 x 39 mm	112 x 66 x 16 mm	160 x 115 x 37 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Russian, Portuguese, Romanian, Ukrainian, Hungarian, Italian
Manufacturer / Brand	DAHUA	...	TP-LINK	DAHUA
Guarantee	5 years	2 years	3 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00